


Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

T23SR6W



from which

A fir, 12 ins. diam., bears N. $74\frac{1}{2}^\circ$ E., 44 lks. dist.,
mkd. $\frac{1}{4}$ S32 BT.

A fir, 24 ins. diam., bears N. 73° W., 45 lks. dist.,
mkd. $\frac{1}{4}$ S31 BT.

Descend 400 ft. over NW. slope.

48.33 Bear Creek, 10 lks. wide, course SE.; asc. 63 ft. over SW. slope.


49.38 Graded road, 30 lks. wide, bears NW. and SE.; asc. 131 ft. over SW. slope.

54.02 Road, unimproved, bears NW. and SE.; asc. 405 ft. over SW. slope.

80.14 Point for the cor. of secs. 29, 30, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23SR6W



from which

A fir, 10 ins. diam., bears N. $64\frac{1}{2}^\circ$ E., 114 lks. dist.,
mkd. T23S R6W S29 BT.

A fir, 13 ins. diam., bears S. 66° E., 207 lks. dist.,
mkd. T23S R6W S32 BT.

A fir, 13 ins. diam., bears S. 71° W., 72 lks. dist.,
mkd. T23S R6W S31 BT.

A fir, 13 ins. diam., bears N. 27° W., 72 lks. dist.,
mkd. T23S R6W S30 BT.

Land, mountainous. Soil, sandy loam, rock outcroppings. Timber, fir, hemlock, and cedar. Undergrowth, vine maple, poison oak, and salal.

From the cor. of secs. 28, 29, 32, and 33.

S. $88^\circ 57'$ W., bet. secs. 29 and 32.

Descend 108 ft. over NW. slope.

5.55 Creek, 5 lks. wide, course S. 35° W.; asc. 16 ft. over SE. slope.

6.91 Spur, slopes S.; desc. 56 ft. over W. slope.

14.65 Creek, 5 lks. wide, course S. 20° W.; asc. 430 ft. over E. slope.

24.10 Spur, slopes S. 20° E.; asc. 133 ft. over SE. slope.

33.08 Ridge, bears S. 25° E. and N. 25° W.; desc. 235 ft. over SW. slope.