

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

A fir, 20 ins. diam., bears N. 21° E., 73 lks. dist.,
mkd. $\frac{1}{4}$ S20 BT.

A fir, 33 ins. diam., bears S. 49° W., 74 lks. dist.,
mkd. $\frac{1}{4}$ S29 BT.

Descend 161 ft. along S. slope.

58.41 Spur, slopes SW.; desc. 503 ft. over SW. slope.

79.05 Creek, 5 lks. wide, course S.; asc. 122 ft. over E. slope.

81.36 The cor. of secs. 19, 20, 29, and 30.

Land, mountainous. Soil, sandy loam, rock outcroppings. Timber,
fir, hemlock, and cedar. Undergrowth, poison oak, salal, vine
maple, madrone, and alder.

S. 88°57' W., bet. secs. 19 and 30.

Descend 122 ft. over S. slope.

9.98 Creek, 3 lks. wide, course SE.; asc. 437 ft. over E. slope,
changing to SE. slope.

18.05 Spur, slopes S.; asc. 47 ft. over SE. slope.

21.26 Spur, slopes S.; road, unimproved, 20 lks. wide, bears N. and S.;
desc. 66 ft. over NW. slope.

24.79 Gully, drains SE.; asc. 139 ft. over SE. slope.

30.65 Ridge, bears NE. and SW.; desc. 103 ft. over NW. slope.

34.94 Road, unimproved, 30 lks. wide, bears NE. and SW.; desc. 164 ft.
over NW. slope.

40.58 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate
distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the
ground, with brass cap mkd.

T23SR6W

$\frac{1}{4}$ S 19
S 30

1957

from which

A fir, 11 ins. diam., bears N. 56° E., 32 lks. dist.,
mkd. $\frac{1}{4}$ S19 BT.

A fir, 11 ins. diam., bears S. 18° E., 53 lks. dist.,
mkd. $\frac{1}{4}$ S30 BT.

Descend 324 ft. over NW. slope.

67.07 Creek, 3 lks. wide, course W.; desc. 65 ft. over N. slope.

79.03 The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp.

Land, mountainous. Soil, sandy loam, sandstone, outcroppings.
Timber, fir, hemlock, and cedar. Undergrowth, vine maple, salal,
madrone, and laurel.