

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

From the cor. of secs. 19, 20, 29, and 30.

N. $25^{\circ}16'$ E., bet. secs. 19 and 20.

Ascend 100 ft. over SE. slope.

4.03 Ridge, bears NW. and SE.; desc. 73 ft. along E. slope.

7.50 Creek, 7 lks. wide, course SE.; asc. 360 ft. along broken E. slope.

32.57 Spur, slopes NE.; 253 ft. over NE. slope.

43.48 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23SR6W

from which

A fir, 26 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 30 lks. dist.,
mkd. $\frac{1}{4}$ S20 BT.A hemlock, 8 ins. diam., bears N. 36° W., 16 lks. dist.,
mkd. $\frac{1}{4}$ S19 BT.

Ascend 22 ft. over S. slope.

45.76 Road, unimproved, 20 lks. wide, bears NE. and SW.; asc. 5 ft. over S. slope.

46.75 Ridge, bears E. and W.; desc. 496 ft. over NW. slope.

65.22 Point for the N $1/16$ sec. cor. of secs. 19 and 20.

Set an iron post, 30 ins. long, 2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23SR6W

from which

A fir, 25 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ E., 95 lks. dist.,
mkd. N $1/16$ S20 BT.A hemlock, 19 ins. diam., bears S. 49° W., 34 lks. dist.,
mkd. N $1/16$ S19 BT.

Descend 92 ft. over NW. slope.

68.00 Gully, drains NW.; asc. 28 ft. over SW. slope.

72.74 Head of gully, drains NW.; desc. 226 ft. over NW. slope.

81.23 Creek, 3 lks. wide, course W.; asc. 94 ft. over S. slope, changing to SW. slope.