

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS  
86.96

The cor. of secs. 17, 18, 19, and 20, determined at record distances from two of the original bearing trees:

A fir, 28 ins. diam., bears S. 42° W., 20 lks. dist.,  
mkd. T23 R6 19 BT. (Record bearing, S. 32° W.)

A fir, 28 ins. diam., bears N., 9 lks. dist.,  
mkd. T23 R6 18 BT. (Record bearing, N. 12° W.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground,  
with brass cap mkd.

T23SR6W  
S18|S17  
S19|S20  
1957

from which

A fir, 26 ins. diam., bears N. 48½° E., 46 lks. dist.,  
mkd. T23S R6W S17 BT.

A fir, 26 ins. diam., bears S. 24½° E., 205 lks. dist.,  
mkd. T23S R6W S20 BT.

A fir, 21 ins. diam., bears S. 38° W., 46 lks. dist.,  
mkd. T23S R6W S19 BT.

A fir, 18 ins. diam., bears N. 51° W., 29 lks. dist.,  
mkd. T23S R6W S18 BT.

Land, mountainous. Soil, sandy loam. Timber, fir, hemlock, and cedar. Undergrowth, poison oak, salal, vine maple, and madrone.

From the cor. of secs. 16, 17, 20, and 21.

N. 88°15' W., bet. secs. 17 and 20.

Ascend 220 ft. over steep SE. slope.

11.60 Ravine, drains S. 40° E.; asc. 383 ft. over SE. slope.

17.53 Point for the E 1/16 sec. cor. of secs. 17 and 20.

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground,  
with brass cap mkd.

E 1/16  $\frac{S\ 17}{S\ 20}$   
1957

from which

A fir, 19 ins. diam., bears N. 16° E., 13 lks. dist.,  
mkd. E 1/16 S17 BT.

A fir, 19 ins. diam., bears S. 48½° E., 3 lks. dist.,  
mkd. E 1/16 S20 BT.

Ascend 12 ft. over SE. slope.

27.14 Blunt spur, slopes S.; desc. 118 ft. over SW. slope.

35.06 Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground,  
and in a mound of stone, 3 ft. base, to top, with brass cap mkd.