

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T23SR6W

$\frac{1}{4}$  S 18

S 19

1957

from which

A fir, 7 ins. diam., bears N. 82° E., 69 lks. dist.,  
mkd.  $\frac{3}{4}$  S18 BT.

A fir, 6 ins. diam., bears S. 50° E., 54 lks. dist.,  
mkd.  $\frac{1}{4}$  S19 BT.

Descend 26 ft. over NE. slope.

- 62.00 Spur, slopes NW.; desc. 702 ft. over broken SW. slope.
- 101.10 Creek, 5 lks. wide, course N. 30° W.; asc. 132 ft. over NE. slope.
- 108.35 Spur, slopes N. 25° W.; desc. 46 ft. over SW. slope.
- 112.25 Creek, 1 lk. wide, course N. 65° W.; asc. 34 ft. over NE. slope.
- 116.57 The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp.  
Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, salal, poison oak, vine maple, arrowwood, madrone, alder, and laurel.

From the cor. of secs. 17, 18, 19, and 20.

N. 0°12' W., bet. secs. 17 and 18.

Ascend 2 ft. over SW. slope.

- 1.00 Top of ascent on N. slope; desc. 122 ft. over N. slope.
- 3.88 Creek, 2 lks. wide, course W.; asc. 116 ft. over S. slope.
- 8.25 Spur, slopes SW.; desc. 48 ft. along broken W. slope.
- 13.35 Creek, 2 lks. wide, course W.; asc. 212 ft. over SW. slope.
- 34.02 Spur ridge, bears N. 42° W. and S. 48° E.; desc. 80 ft. over N. slope.
- 36.01 The  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, determined at record distance from the original bearing trees:  
  
A fir, 20 ins. diam., bears S. 28° E., 8 lks. dist.,  
mkd.  $\frac{3}{4}$  S BT. (Record bearing, S. 62 $\frac{1}{2}$ ° E.)  
  
A fir, 50 ins. diam., bears N. 80° W., 45 lks. dist.,  
with a chopped out blaze. (Record bearing, N. 20° W.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T23SR6W

$\frac{1}{4}$   
S18 | S17

1957