

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

Set an iron post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T23SR6W  
 $\frac{1}{4}$   $\frac{S}{S}$   $\frac{8}{17}$   
 1957

FD OK 2/93  
 28 Nov 1949  
 CS 63/149

from which

A chinquapin, 6 ins. diam., bears N. 4° E., 70 lks. dist., mkd.  $\frac{1}{4}$  S8 BT.

A fir, 6 ins. diam., bears S. 88° W., 14 lks. dist., mkd.  $\frac{1}{4}$  S17 BT.

Descend 750 ft. over W. slope, changing to SW. slope.

78.20 Creek, 15 lks. wide, course N. 15° W.; asc. 450 ft. over NE. slope, changing to N. slope.

85.56 The cor. of secs. 7, 8, 17, and 18.

Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, salal, poison oak, vine maple, alder, madrone, and laurel.

N. 85°23' W., bet. secs. 7 and 18.

Ascend 270 ft. along N. slope, changing to NE. slope.

4.60 Trail on ridge, bears N. 10° W. and S. 15° E.; desc. 524 ft. over W. slope.

27.30 Creek, 12 lks. wide, course N. 15° W.; asc. 501 ft. over NE. slope.

42.74 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23SR6W  
 $\frac{1}{4}$   $\frac{S}{S}$   $\frac{7}{18}$   
 1957

from which

A fir, 26 ins. diam., bears N. 5° W., 22 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

A fir, 6 ins. diam., bears S. 35° E., 90 lks. dist., mkd.  $\frac{1}{4}$  S18 BT.

This cor. monument is established on spur, slopes N. 80° E.

Ascend 134 ft. along N. slope.

54.00 Ridge, bears N. 30° W. and S. 30° E.; desc. 21 ft. over W. slope.

55.50 Trail, bears S. 20° E. and N. 20° W.; desc. 60 ft. over W. slope.

81.30 The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp.

Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, salal, poison oak, vine maple, and madrone.