

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

From the cor. of secs. 5, 6, 7, and 8.

N. 19°16' E., bet. secs. 7 and 8.

Descend 28 ft. along E. slope.

1.80 Spur, slopes N. 45° E.; desc. 379 ft. over NW. slope.

9.00 Ravine, drains N. 55° E.; desc. 124 ft. over E. slope.

17.25 W. edge of creek, course N. 20° E.; asc. 5 ft. along E. slope.

25.32 Spur, slopes S. 50° E.; desc. 73 ft. along E. slope.

35.25 Creek, 8 lks. wide, course N. 35° W.; asc. 54 ft. over NW. slope.

37.065 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T23SR6W

$$\begin{array}{c} \frac{1}{4} \\ | \\ S7 | S8 \\ | \\ 1957 \end{array}$$

from which

A hemlock, 6 ins. diam., bears N. 22° E., 40 lks. dist., mkd. $\frac{1}{4}$ S8 BT.A cedar, 6 ins. diam., bears S. 55° W., 48 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

Ascend 107 ft. over NW. slope, changing to W. slope.

53.40 Creek, 1 lk. wide, course N. 20° W.; desc. 58 ft. over NW. slope.

63.55 Road, unimproved, 30 lks. wide, bears N. 27° W. and S. 27° E.; spur, slopes N. 30° W.; desc. 85 ft. over N. slope.

70.05 Road, unimproved, 30 lks. wide, bears N. 80° W. and S. 80° E.; desc. 28 ft. over N. slope.

71.94 Creek, 12 lks. wide, course S. 85° W.; asc. 15 ft. over N. slope.

74.13 The cor. of secs. 5, 6, 7, and 8, determined at record distance from the remaining original bearing trees:

A fir, 110 ins. diam., bears N. 12° E., 14 lks. dist., mkd. T23S R6W S5 CS BT.

A fir snag, burned, bears S. 70° E., 36 lks. dist., no legible marks. (Record bearing, S. 20° E.)

A fir, dead and down, bears S. 47° W., mkd. T23R6 BT.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T23SR6W

$$\begin{array}{c} S6 | S5 \\ S7 | S8 \\ 1955 \end{array}$$

from which