

Dependent Resurvey of the Subdivisional Lines, T. 23 S., R. 6 W.

CHAINS

A hemlock, 6 ins. diam., bears N. 64° E., 75 lks. dist.,
mkd. T23S R6W S5 BT.

A hemlock, 6 ins. diam., bears S. 6° E., 102 lks. dist.,
mkd. T23S R6W S8 BT.

A cedar, 10 ins. diam., bears S. 42½° W., 106 lks. dist.,
mkd. T23S R6W S7 BT.

A hemlock, 10 ins. diam., bears N. 43° W., 70 lks. dist.,
mkd. T23S R6W S6 BT.

Land, mountainous. Soil, clay loam. Timber, fir, hemlock, and cedar. Undergrowth, salal, poison oak, vine maple, alder, arrowwood, and madrone.

From the cor. of secs. 4, 5, 8, and 9.

N. 88°48' W., bet. secs. 5 and 8.

Ascend 27 ft. over E. slope.

0.75 Ridge, bears N. and S.; desc. 86 ft. over SW. slope.

3.65 Swale, drains S.; asc. 105 ft. over SE. slope.

6.70 Spur, slopes S.; desc. 249 ft. along broken S. slope.

23.25 Spur, slopes S. 50° W.; desc. 210 ft. over NW. slope.

30.56 Ravine, drains S. 45° W.; asc. 55 ft. over SE. slope.

32.40 Spur, slopes S. 45° W.; desc. 126 ft. over NW. slope.

37.03 Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, and in a mound of stone, 6 ft. base, to top, with brass cap mkd.

T23SR6W	FD OK 2/93
¼ S 5	BY HERRING
¼ S 8	C.S. 63/149
1957	

from which

A hemlock, 12 ins. diam., bears N. 7° W., 41 lks. dist.,
mkd. ¼ S5 BT.

A cedar, 12 ins. diam., bears S. 13° E., 12 lks. dist.,
mkd. ¼ S8 BT.

Over level land.

37.10 Creek, 2 lks. wide, course S. 45° W.; asc. 98 ft. over SE. slope.

40.36 Spur, slopes S.; desc. 153 ft. over SW. slope.

53.00 Road, improved, 50 lks. wide, bears S. 60° E. and N. 60° W.;
thence over level land.

69.90 Right bank of creek, 18 lks. wide, course N. 10° W.; asc. 7 ft.
along S. slope.

71.05 Right bank of creek, course S. 30° W. curves to W.; asc. 7 ft.
over S. slope.