

County Surveyor's Record, Douglas County, Oregon
2

Dependent Resurvey of a Portion of the N. Bdy., T. 26 S., R. 2 W.

CHAINS

A basalt stone, 4 x 3 $\frac{1}{2}$ x 3 ft. above ground, bears S. 20° E., 54 lks. dist., mkd. T26S R2W S2 BS on NW. face.

A fir, 40 ins. diam., bears S. 82 $\frac{1}{2}$ ° W., 248 $\frac{1}{2}$ lks. dist., with a healed blaze. This tree has been re-blazed in 1959 above the healed blaze and scribed S3 T26S R2W RE4079. (Record dist., 256 lks.)

and a locally established bearing tree marked in 1959

A fir, 33 ins. diam., bears S. 44 $\frac{1}{2}$ ° E., 56 lks. dist., mkd. S2 T26S R2W RE4079 BT on unhealed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 25\ S\ R\ 2\ W \\ \quad \quad \quad S\ 35 \\ \quad \quad \quad \hline \quad \quad \quad S\ 3\ |S\ 2 \\ T\ 26\ S\ R\ 2\ W \\ \quad \quad \quad 1959 \end{array}$$

Deposit the original corner stone alongside the iron post.

N. 89°06' W., along the N. bdy. of sec. 3, marking and blazing the true line.

Descend 66 ft. over SW. slope, through scattered timber and dense undergrowth.

2.55 Creek, 2 lks. wide, course S.; asc. 6 ft. along S. slope.

3.13 Find no evidence of the closing cor. of secs. 34 and 35, T. 25 S., R. 2 W.

4.05 Top of ascent, slopes S.; desc. 172 ft. over W. slope, changing to SW. slope.

20.85 Creek, 5 lks. wide, course S.; asc. 92 ft. over SE. slope.

23.00 Dirt access road, 15 lks. wide, bears N. and S. 30° W.

26.00 Top of ascent, slopes S.; desc. 23 ft. along S. slope.

30.35 Foot of descent, slopes S.; asc. 20 ft. along broken S. slope.

39.10 The $\frac{1}{4}$ sec. cor. of sec. 3 only, monumented by Collier with a basalt stone, 16 x 10 x 4 ins., firmly set, 10 ins. in the ground, marked $\frac{1}{4}$ on S. face, alongside of which has been driven an aluminum rod, $\frac{1}{2}$ in. diam., protruding 12 ins. above ground; from the corner point a locally established bearing tree:

A fir, 25 ins. diam., bears S. 55° W., 120 lks. dist., mkd. T26S R2W $\frac{1}{4}$ S3 BT on an unhealed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4}\ S\ 3 \\ T\ 26\ S\ R\ 2\ W \\ \quad \quad \quad 1959 \end{array}$$