

Dependent Resurvey of a Portion of the N. Bdy., T. 26 S., R. 2 W.

CHAINS

from which a new bearing tree

A fir, 34 ins. diam., bears S. 29° E., 220 lks. dist.,
mkd. $\frac{1}{4}$ S3 BT.

Deposit the original corner stone and the aluminum rod
alongside the iron post.

N. 89°56' W., beginning new measurement.

Descend 273 ft. along S. slope, changing to SW. slope, through
heavy timber and dense undergrowth.

4.45 Dirt access road, 15 lks. wide, bears S. 60° E. and S. 60° W.

16.05 Branch of Honey Creek, 5 lks. wide, course S.; asc. 343 ft. over E.
slope, changing to SE. slope.

38.99 The cor. of secs. 3 and 4 only, perpetuated with an unmarked basalt
stone, 14 x 10 x 8 ins., firmly set, at record distance from each
of the bearing trees marked by Collier in 1913:

A fir, 40 ins. diam., bears S. 16 $\frac{3}{4}$ ° E., 512 lks. dist.,
with scribe marks S 3 B visible on an opened blaze.
(Record bearing, S. 12° E.)

A down and rotted fir, 14 ins. diam., bears S. 23 $\frac{1}{4}$ ° W.,
399 lks. dist., with scribe marks BT and other illegible
marks visible on opened blaze. (Record bearing, S. 22° W.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the
ground, with brass cap mkd.

T 25 S R 2 W
 S 34
 S 4 | S 3
T 26 S R 2 W
 1959

from which

A fir, 14 ins. diam., bears S. 14 $\frac{1}{4}$ ° W., 53 $\frac{1}{2}$ lks. dist.,
mkd. T26S R2W S4 BT.

Deposit the basalt stone alongside the iron post.

Land, mountainous. Soil, rocky clay and clay loam. Timber, fir,
hemlock, pine, chinquapin, maple, alder, dogwood and madrone; under-
growth, salal, Oregon grape, rhododendron, vine maple, manzanita,
fern, poison oak, willow and hazel.

From the cor. of secs. 4 and 5 only, on the N. bdy. of the Tp.,
determined at record bearing and distance from three remaining
original bearing trees and a bearing tree established in 1913:

A fir, 30 ins. diam., bears N. 65° E., 28 lks. dist.,
with illegible bark-scribe marks visible.

A fir, 25 ins. diam., bears S. 10° E., 22 lks. dist.,
bark scribed T26 4 BT and other illegible scribe marks.