

## Dependent Resurvey of a Portion of the N. Bdy., T. 26 S., R. 2 W.

CHAINS

A yew, 10 ins. diam., bears S. 60° W., 51 lks. dist.,  
mkd. T26S R2W S5 BT on partially healed blaze.  
(1913 bearing tree)

A fir, 38 ins. diam., bears N. 55° W., 5 lks. dist.,  
bark-scribed 2 R2 6 together with other illegible  
scribe marks.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the  
ground, with brass cap mkd.

T 25 S R 2 W  
    S 33  
    S 5 | S 4  
T 26 S R 2 W  
    1959

S. 89°27' W., along the N. bdy. of sec. 5.

Descend 59 ft. over NW. slope, through heavy timber and dense  
undergrowth.

- 2.10 Creek, 2 lks. wide, course N.; asc. 218 ft. over NE. slope.
- 6.00 Find no evidence of the closing cor. of secs. 32 and 33, T. 25 S.,  
R. 2 W.
- 8.15 Spur, slopes N.; desc. 50 ft. over NW. slope.
- 12.15 Foot of descent, slopes N.; asc. 112 ft. over NE. slope.
- 17.80 Spur, slopes N.; desc. 41 ft. over NW. slope.
- 19.70 Ravine, drains N.; asc. 270 ft. over NE. slope, changing to E. slope
- 28.10 Ridge, bears NW. and SE.; desc. 290 ft. over SW. slope.
- 41.04 Point for the  $\frac{1}{4}$  sec. cor. of sec. 5 only, at proportionate distance;  
there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the  
ground, and in a mound of stone, 2 ft. base, to top, with brass cap  
mkd.

T 26 S R 2 W  
     $\frac{1}{4}$  S 5  
    1959

from which

A fir, 15 ins. diam., bears S. 50° E., 26 lks. dist.,  
mkd.  $\frac{1}{4}$  S5 BT.

A fir, 10 ins. diam., bears S. 68½° W., 29 lks. dist.,  
mkd.  $\frac{1}{4}$  S5 BT.

Descend 799 ft. over SW. slope.

- 65.70 Creek, 6 lks. wide, course NW.; asc. 314 ft. over NE. slope.
- 82.08 The cor. of secs. 5 and 6 only, reestablished by Collier in 1913,  
monumented by a fir, 13 ins. diam., with a healed blaze and 1 notch  
on the W., and a healed blaze and 5 notches on the E. side, from  
which the 1913 bearing trees: