

12724

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy., T. 26 S., R. 2 W.

CHAINS 9.45	North Umpqua Highway, bituminous pavement, 40 lks. wide, bears SE. and NW. curving to W.					
17.00	Three-wire transmission line, bears E. and W.					
20.95	Abandoned dirt access road, 15 lks. wide, bears NW. and SE.					
39.60	Dirt access road, 30 lks. wide, bears NW. and SE.					
40.04	<p>The cor. of secs. 1, 6, 7, and 12, perpetuated with an iron pipe, 2 ins. diam., protruding 36 ins. above ground, firmly set, at record bearing and distance from each of the two remaining original bearing trees:</p> <p style="margin-left: 40px;">A cedar, 36 ins. diam., bears S. 60° W., 30 lks. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 30 ins. diam., bears N. 46° W., 88 lks. dist., with scribe marks T26S R3W S1 visible on a partially opened blaze.</p> <p>and locally established bearing trees</p> <p style="margin-left: 40px;">A hemlock, 10 ins. diam., bears N. 37° E., 17½ lks. dist., mkd. with a partially healed blaze and a nail stamped W on head. Re-mark this tree T26S R2W S6 BT.</p> <p style="margin-left: 40px;">A cedar, 12 ins. diam., bears S. 73° E., 41 lks. dist., mkd. with a nail stamped W on head. Re-mark this tree T26S R2W S7 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <table style="margin: auto;"> <tr><td>T 26 S</td></tr> <tr><td>R 3 W R 2 W</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 1 S 6</td></tr> <tr><td style="border-left: 1px solid black; border-right: 1px solid black;">S 12 S 7</td></tr> <tr><td>1959</td></tr> </table> </div> <p style="margin-left: 40px;">Deposit the iron pipe alongside the iron post.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, pine, maple, madrone, chinquapin, ash and dogwood; undergrowth, hazel, ocean spray, huckleberry, vine maple, rhododendron, manzanita, salal, blackberry and poison oak.</p>	T 26 S	R 3 W R 2 W	S 1 S 6	S 12 S 7	1959
T 26 S						
R 3 W R 2 W						
S 1 S 6						
S 12 S 7						
1959						

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W. (Restoring the 1883 survey by John A. McQuinn and the 1918 revision survey by Fred Mensch)

From the cor. of secs. 14, 15, 22, and 23, monumented with a basalt stone, 8 x 6 x 6 ins., set by Gibbs in 1909, with 3 notches on the S. and 2 notches on the E. edge; perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1957, with an iron post, 1½ ins. diam., protruding 8 ins. above ground, firmly set alongside the marked stone, with brass cap mkd.

T 26 S R 2 W
SEC 15 14
22 23
1957

FO. OK 2/2004
D. EDWARDS M1A3-66