

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

from which 1883 bearing trees

A sawed fir stump, 28 ins. diam., bears S.  $46\frac{3}{4}^{\circ}$  E., 86 lks. dist., with a healed blaze. (Record bearing, S.  $50^{\circ}$  E.)

A fir, 25 ins. diam., bears S.  $71\frac{1}{2}^{\circ}$  W.,  $52\frac{1}{2}$  lks. dist., with a healed blaze. (Record bearing and dist., S.  $70^{\circ}$  W., 54 lks.)

and 1918 bearing trees

A fir, 16 ins. diam., bears N.  $51\frac{1}{2}^{\circ}$  E., 65 lks. dist., with scribe marks 26 visible on a partially opened blaze. (Record dist., 64 lks.)

A chopped madrone stump, 7 ins. diam., bears S.  $35\frac{3}{4}^{\circ}$  W.,  $23\frac{1}{2}$  lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record bearing and dist., S.  $33^{\circ}$  W., 25 lks.)

A fir, 24 ins. diam., bears N.  $70\frac{1}{2}^{\circ}$  W., 75 lks. dist., with a healed blaze.

and County Surveyor's bearing tree


A cedar, 14 ins. diam., bears S.  $1\frac{1}{2}^{\circ}$  E.,  $194\frac{1}{2}$  lks. dist., mkd. T26S R2W S23 CS BT.

N.  $1^{\circ}36'$  E., bet. secs. 14 and 15, marking and blazing the true line.

Ascend 98 ft. over SE. slope, through heavy timber and dense undergrowth.

- 5.15 Leave timber, enter pasture land, edge bears NE. and SW.
- 15.10 Leave pasture land, enter timber, edge bears E. and W.
- 19.40 Top of ascent, slopes E.; desc. 37 ft. over NE. slope.
- 23.60 Dirt access road, 25 lks. wide, bears NW. and SE.
- 25.50 Creek, 3 lks. wide, course SE.; asc. 127 ft. over SE. slope.
- 27.32 Three-wire transmission line, bears E. and W.
- 28.77 Three-wire transmission line, bears E. and W.
- 40.38 Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, and in a mound of stone,  $1\frac{1}{2}$  ft. base, to top, with brass cap mkd.

T 26 S R 2 W



from which

A fir, 8 ins. diam., bears East, 50 lks. dist., mkd.  $\frac{1}{4}$  S14 BT.

A fir, 10 ins. diam., bears N.  $86^{\circ}$  W., 80 lks. dist., mkd.  $\frac{1}{4}$  S15 BT.