

County Surveyor's Record, Douglas County, Oregon

13726

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

From this point the NE. cor. of an abandoned wood frame building, bears S. 33°31' W., 85 lks. dist., dimensions 13 x 12 ft., long-side bears South.


From the same point the NW. cor. of an abandoned wood frame building, bears S. 37°17' E., 109 lks. dist., dimensions 14½ x 10½ ft., long-side bears East.

Ascend 199 ft. over SE. slope.

56.95 Dirt access road, 20 lks. wide, bears SW. and E. curving to SE.

60.57 Point for the N 1/16 sec. cor. of secs. 14 and 15.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A fir, 16 ins. diam., bears N. 72° E., 15 lks. dist., mkd. N 1/16 S14 BT.

A fir, 22 ins. diam., bears N. 85° W., 21 lks. dist., mkd. N 1/16 S15 BT.

Ascend 59 ft. over SE. slope.

67.75 Spur, slopes SE.; desc. 20 ft. over NE. slope.

70.02 Creek, 4 lks. wide, course SE.; asc. 81 ft. over SE. slope.

72.70 Leave timber, enter logged area, edge bears E. and W.

80.76 The cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by Ben B. Irving, County Surveyor, in 1945, monumented with a basalt stone, 16 x 6 x 4 ins., with an X on top, 4 notches on S. and 2 notches on the E. edge, set in a mound of stone, 2 ft. base, 1 ft. high, from which the original bearing trees:

A fir, 30 ins. diam., bears N. 63½° E., 53 lks. dist., bark scribed by County Surveyor, T26S R2W S11 CS BT. (Record bearing, N. 65° E.)

A sawed fir stump, 36 ins. diam., bears S. 22¾° E., 99 lks. dist., no marks visible. (Record bearing and dist., S. 20° E., 110 lks.)

A sawed fir stump, 30 ins. diam., bears S. 27¼° W., 56 lks. dist., bark scribed by County Surveyor S15 CS BT. (Record bearing and dist., S. 30° W., 53 lks.)

A fir, 36 ins. diam., bears N. 40¾° W., 16 lks. dist., bark scribed by County Surveyor T26S R2W S10 CS BT. (Record bearing and dist., N. 50° W., 15 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.