

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

T 26 S R 2 W
 S 10 | S 11
 S 15 | S 14
 1959

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the cor.

Deposit the basalt stone alongside the iron post.

Land, rolling hills. Soil, rocky loam. Timber, scattering fir, cedar, pine, madrone, and maple; undergrowth, huckleberry, poison oak, ocean spray, hazel, salal, manzanita, vine maple, rhododendron, ceanothus and Oregon grape.

From the cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by Ben B. Irving, County Surveyor, in 1927, monumented with a mound of stone, $1\frac{1}{2}$ ft. base, 1 ft. high; from which the only remaining original bearing tree:

A fir, 57 ins. diam., bears N. 35° E., 79 lks. dist., with scribe marks T26 visible on an opened blaze.

and County Surveyor's bearing trees

A fir, 36 ins. diam., bears N. $78\frac{1}{2}^\circ$ E., 96 lks. dist., with a healed blaze.

A fir, 45 ins. diam., bears S. $66\frac{1}{2}^\circ$ E., 100 lks. dist., bark scribed T26S R2W S11 CS BT.

A fir, 17 ins. diam., bears S. $62\frac{1}{2}^\circ$ W., 36 lks. dist., with a healed blaze.

A fir, 41 ins. diam., bears N. $9\frac{1}{2}^\circ$ W., 102 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 26 S R 2 W
 S 3 | S 2
 S 10 | S 11
 1959

N. $1^\circ 10'$ E., bet. secs. 2 and 3.

Descend 383 ft. over NW. slope, through heavy timber and dense undergrowth.

- 0.85 Dirt access road, 15 lks. wide, bears N. 75° E. and S. 75° W.
- 21.60 Creek, 1 lk. wide, course W.; asc. 32 ft. over SW. slope.
- 23.60 Top of ascent, slopes W.; desc. 69 ft. over NW. slope.
- 27.65 Creek, 4 lks. wide, course S. 60° W.; asc. 316 ft. over S. slope, changing to SW. slope.
- 31.95 Skid road, 10 lks. wide, bears E. and SW.