

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS
42.68


The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, restored at proportionate distance by R. G. Lecklider, in 1959, monumented with a $1\frac{3}{4}$ in. iron pipe, protruding 16 ins. above ground, firmly set in a mound of stone, 2 ft. base, 1 ft. high, from which:

A fir, 8 ins. diam., bears N. $66\frac{1}{2}^\circ$ E., 16 lks. dist.,
mkd. $\frac{1}{4}$ S2 RE4079 BT.

A fir, 20 ins. diam., bears S. 70° W., 14 lks. dist.,
mkd. $\frac{1}{4}$ S3 RE4079 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.



Deposit the iron pipe alongside the iron post.

Ascend 256 ft. over S. slope, changing to SW. slope.

- 58.25 Top of ascent, slopes W.; desc. 82 ft. over NW. slope, changing to N. slope.
- 59.65 Dirt access road, 15 lks. wide, bears NE. and SW.
- 61.85 Dirt access road, 15 lks. wide, bears NE. and SW.
- 66.35 Leave timber, enter meadow, edge bears E. and W.
- 68.35 Leave meadow, enter timber, edge bears E. and W.
- 71.57 Creek, 1 lk. wide, course W.; desc. 10 ft. along W. slope.
- 76.56 Dirt access road, 15 lks. wide, bears N. 60° W. and S. 60° E.
- 78.06 Foot of descent, slopes W.; asc. 151 ft. over SW. slope.
- 84.64 The cor. of secs. 2 and 3 only, on the N. bdy. of the Tp., previously described.

Land, mountainous. Soil, clay loam and rocky clay. Timber, fir, hemlock, cedar, chinquapin, maple, alder, madrone and dogwood; undergrowth, salal, Oregon grape, vine maple, rhododendron, hazel, huckleberry, fern, willow and arrowwood.

From the cor. of secs. 14, 15, 22, and 23.

S. $89^\circ 46'$ W., bet. secs. 15 and 22.

Ascend 136 ft. over SE. slope, through heavy timber and scattering undergrowth.

- 23.80 Spur, slopes S.; desc. 186 ft. along S. slope, changing to SW. slope.

- 39.44 The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., 4 ins. above ground, firmly set, in a mound of stone, 3 ft. base, to top, set by Mensch in 1918, with brass cap mkd.