

County Surveyor's Record, Douglas County, Oregon

15

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

Land, rolling hills. Soil, rocky clay. Timber, fir, hemlock, cedar, sugar pine, chinquapin, madrone, maple, oak, alder and dogwood; undergrowth, salal, Oregon grape, vine maple, rhododendron, poison oak, manzanita, huckleberry and hazel.

From the cor. of secs. 10, 11, 14, and 15.

S. 89°05' W., bet. secs. 10 and 15.

Ascend 49 ft. over SE. slope, through 2nd growth timber and dense undergrowth.

10.88 Top of ascent, slopes S.; desc. 25 ft. over SW. slope.

17.25 Creek, 5 lks. wide, course SE.; asc. 29 ft. over SE. slope.

19.86 Point for the E 1/16 sec. cor. of secs. 10 and 15.

Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. below the surface of the E. edge of a gravel access road, 20 lks. wide, bears NW. and S. curving to SE., with brass cap mkd.

$$E \frac{1}{16} \begin{array}{l} S \ 10 \\ S \ 15 \end{array} \\ 1959$$

from which

A fir, 9 ins. diam., bears N. 42½° E., 75 lks. dist.,
mkd. E 1/16 S10 BT.

A fir, 10 ins. diam., bears S. 41¼° E., 78 lks. dist.,
mkd. E 1/16 S15 BT.

Leave timber, enter pasture land, edge bears N. and S.; asc. 8 ft. along S. slope.

24.25 Top of ascent, slopes SW.; desc. 109 ft. over SW. slope.

27.00 Leave pasture land, enter timber and dense undergrowth, edge bears NE. and SW.

35.67 Creek, 5 lks. wide, course S.; asc. 2 ft. over E. slope.

37.67 Creek, 2 lks. wide, course S.; asc. 23 ft. over SE. slope.

39.72 Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, and in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd.

$$T \ 26 \ S \ R \ 2 \ W \ \begin{array}{l} \text{END OK 6-99 BY K. DEGRADT} \\ M131-SB \\ \frac{1}{4} \begin{array}{l} S \ 10 \\ S \ 15 \end{array} \\ 1959 \end{array}$$

from which

A fir, 40 ins. diam., bears N. 27¼° W., 44½ lks. dist.,
mkd. ¼ S10 BT.

A fir, 16 ins. diam., bears S. 65¼° E., 137 lks. dist.,
mkd. ¼ S15 BT.

Ascend 386 ft. over SE. slope.