

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

A fir, 12 ins. diam., bears S. $48\frac{1}{2}^\circ$ E., 7 lks. dist.,
mkd. $\frac{1}{4}$ S10 BT.

A fir, 14 ins. diam., bears N. $25\frac{1}{4}^\circ$ W., 16 lks. dist.,
mkd. $\frac{1}{4}$ S9 BT.

The corner falls at top of a bluff, edge bears N. and S. curving to SE.; continue along top of bluff.

43.57 Leave top of bluff, edge bears NE. and S.; descend 382 ft. over NW. slope.

59.85 Creek, 8 lks. wide, course W.; asc. 221 ft. over S. slope, changing to SW. slope.

66.30 Spur, slopes W.; asc. 191 ft. over SW. slope.

83.14 Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 26 S R 2 W	
S 4	S 3
S 9	S 10
1959	

from which

A fir, 14 ins. diam., bears N. $10\frac{1}{4}^\circ$ E., $48\frac{1}{2}$ lks. dist.,
mkd. T26S R2W S3 BT.

A sugar pine, 19 ins. diam., bears S. $39\frac{1}{4}^\circ$ E., $26\frac{1}{2}$ lks. dist.,
mkd. T26S R2W S10 BT.

A fir, 8 ins. diam., bears S. 37° W., $17\frac{1}{2}$ lks. dist.,
mkd. T26S R2W S9 BT.

A fir, 23 ins. diam., bears N. 34° W., 27 lks. dist.,
mkd. T26S R2W S4 BT.

Land, mountainous. Soil, loam and rocky clay. Timber, fir, hemlock, cedar, pine, chinquapin, madrone, dogwood, maple, alder and oak; undergrowth, salal, rhododendron, vine maple, manzanita, hazel, Oregon grape, huckleberry and poison oak.

From the cor. of secs. 2, 3, 10, and 11.

N. $88^\circ 50'$ W., bet. secs. 3 and 10.

Ascend 24 ft. over E. slope, through heavy timber and scattering undergrowth.

1.70 Dirt access road, 15 lks. wide, bears N. 60° E. and S. 60° W.

4.00 Ridge, bears NE. and SW.; desc. 241 ft. over broken N. slope.

17.60 Creek, 2 lks. wide, course N.; asc. 71 ft. along N. slope.

19.425 Point for the E $1/16$ sec. cor. of secs. 3 and 10.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.