

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

Land, rolling hills. Soil, rocky clay. Timber, fir, hemlock, cedar, sugar pine and scattering maple, madrone, chinquapin and dogwood; undergrowth, huckleberry, poison oak, willow, vine maple, hazel, salal and Oregon grape.

From the cor. of secs. 9, 10, 15, and 16.

S. 88°59' W., bet. secs. 9 and 16.

Descend 39 ft. over SW. slope, through logged area with scattering clumps of undergrowth.

- 3.45 Creek, 3 lks. wide, course S.; desc. 83 ft. over SW. slope, changing to W. slope.
- 11.95 Hogback Creek, 3 lks. wide, course S.; asc. 96 ft. over SE. slope.
- 15.15 Skid road, 15 lks. wide, bears NW. and SE.
- 19.49 Point for the E 1/16 sec. cor. of secs. 9 and 16.
- Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
- $$E \frac{1}{16} \begin{array}{c} S \ 9 \\ S \ 16 \\ 1959 \end{array}$$
- from which
- A cedar, 9 ins. diam., bears N. 82° W., 39 lks. dist., mkd. E 1/16 S9 BT.
- A fir, 8 ins. diam., bears S. 47° W., 23 lks. dist., mkd. E 1/16 S16 BT.
- Ascend 138 ft. over SE. slope.
- 29.55 Ridge, bears N. and S.; desc. 311 ft. over NW. slope.
- 37.60 Ravine, drains NW.; desc. 24 ft. over NW. slope.
- 38.98 The ¼ sec. cor. of secs. 9 and 16, remonumented by Mensch in 1918, with an iron post, 1 in. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.
- $$\frac{1}{4} \begin{array}{c} S \ 9 \\ S \ 16 \\ 1918 \end{array}$$
- from which the 1883 bearing trees
- A dead cedar, 9 ins. diam., bears N. 67¼° E., 23 lks. dist., with scribe mark 4 visible on a partially open blaze. (Mensch's record, bears N. 67° E., 24 lks. dist.)
- A dead cedar, 16 ins. diam., bears S. 57¼° E., 27 lks. dist., with scribe marks ¼ S BT visible on a partially open blaze. (Mensch's record, bears S. 61° E., 28 lks. dist.)
- add two new bearing trees
- A fir, 9 ins. diam., bears N. 16½° E., 31 lks. dist., mkd. ¼ S9 BT.