

County Surveyor's Record, Douglas County, Oregon

23

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS	
	<p>A fir, 9 ins. diam., bears S. $33\frac{3}{4}^{\circ}$ E., 110 lks. dist., mkd. $\frac{1}{4}$ S16 BT.</p> <hr/> <p>S. $88^{\circ}24'$ W., beginning new measurement.</p> <p>Descend 481 ft. over NW. slope, in logged area through dense undergrowth.</p>
6.15	Skid road, 15 lks. wide, bears SE. and NW. curving to W.
13.08	Skid road, 20 lks. wide, bears NE. and SW.
16.50	Honey Creek, 30 lks. wide, course SW.; asc. 35 ft. over SE. slope.
17.45	Honey Creek access road, 20 lks. wide, bears NE. and SW.; also power line, bears NE. and SW.
19.015	Point for the W $1/16$ sec. cor. of secs. 9 and 16.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W $1/16$ $\frac{S\ 9}{S\ 16}$ 1959</p> <p>from which</p> <p>A fir, 10 ins. diam., bears N. 17° E., 19 lks. dist., mkd. W $1/16$ S9 BT.</p> <p>A hemlock, 8 ins. diam., bears S. 65° W., 4 lks. dist., mkd. W $1/16$ S16 BT.</p> <p>Ascend 185 ft. over SE. slope.</p>
23.53	Skid road, 15 lks. wide, bears N. and S.
32.32	Top of ascent, slopes S.; desc. 44 ft. over SW. slope.
34.90	Creek, 4 lks. wide, course SE.; asc. 148 ft. over NE. slope.
38.03	The cor. of secs. 8, 9, 16, and 17.
	<p>Land, rolling hills. Soil, loam and rocky clay. Timber, scattering fir, cedar, pine, madrone, maple and chinquapin; undergrowth, huckleberry, poison oak, ocean spray, hazel, ceanothus, salal, manzanita, rhododendron and vine maple.</p> <hr/> <p>N. $1^{\circ}03'$ E., bet. secs. 8 and 9.</p> <p>Descend 45 ft. along E. slope, through heavy timber and dense undergrowth.</p>
4.73	Creek, 2 lks. wide, course SE.; asc. 352 ft. over S. slope, changing to SE. slope.
13.90	Top of ascent, slopes E.; desc. 9 ft. along E. slope.
15.18	Foot of descent, slopes E.; asc. 127 ft. over SE. slope.
21.23	Point for the S $1/16$ sec. cor. of secs. 8 and 9.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>

FO. OK 3/26/92
BLM
CS 63/140