

County Surveyor's Record, Douglas County, Oregon

25

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

A fir, 36 ins. diam., bears N. $16\frac{1}{2}^{\circ}$ E., 46 lks. dist., mkd. with a nail stamped W on head and driven through the center of a 3 in. bronze disc mkd. Registered Engineer No. 2149.

A fir, 17 ins. diam., bears S. $42\frac{1}{2}^{\circ}$ E., $57\frac{1}{2}$ lks. dist., mkd. with a nail stamped W on head and driven through the center of a 3 in. bronze disc. mkd. Registered Engineer No. 2149.

A fir, 8 ins. diam., bears S. $9\frac{1}{4}^{\circ}$ W., $19\frac{1}{2}$ lks. dist., mkd. with a nail stamped W on head and driven through the center of a 3 in. bronze disc mkd. Registered Engineer No. 2149.

A fir, 27 ins. diam., bears N. $55\frac{1}{4}^{\circ}$ W., 57 lks. dist., mkd. with a nail stamped W on head and driven through the center of a 3 in. bronze disc. mkd. Registered Engineer No. 2149.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 26 S R 2 W	
S 5	S 4
S 8	S 9
1959	

from which new bearing trees

A fir, 32 ins. diam., bears N. $43\frac{3}{4}^{\circ}$ E., $65\frac{1}{2}$ lks. dist., mkd. T26S R2W S4 BT.

A fir, 29 ins. diam., bears S. $20\frac{1}{2}^{\circ}$ E., $56\frac{1}{2}$ lks. dist., mkd. T26S R2W S9 BT.

A fir, 9 ins. diam., bears S. $57\frac{1}{4}^{\circ}$ W., 34 lks. dist., mkd. T26S R2W S8 BT.

A fir, 21 ins. diam., bears N. $83\frac{1}{2}^{\circ}$ W., $63\frac{1}{2}$ lks. dist., mkd. T26S R2W S5 BT.

Reset the wooden stake alongside the iron post.

Land, mountainous. Soil, clay and rocky clay. Timber, fir, hemlock, cedar, madrone, chinquapin, maple, alder, dogwood, and yew; undergrowth, Oregon grape, salal, vine maple, rhododendron, hazel, fern, huckleberry and poison oak.

From the cor. of secs. 3, 4, 9, and 10.

S. $89^{\circ}53'$ W., bet. secs. 4 and 9.

Descend 65 ft. over SW. slope, through heavy timber and scattering undergrowth.

- | | |
|-------|-----------------------------------------------------------------------------------|
| 4.60 | Foot trail, bears NE. and SW. |
| 5.80 | Foot of descent, slopes S.; asc. 38 ft. along S. slope. |
| 11.60 | Top of rock bluff, edge bears N. and S.; deac. 146 ft. over SW. slope. |
| 16.50 | Ravine, drains S.; asc. 35 ft. along S. slope, changing to SE. slope. |
| 21.10 | Spur, slopes SW.; desc. 179 ft. over NW. slope. |
| 27.85 | Honey Creek, 8 lks. wide, course S. 20° W.; asc. 317 ft. over SE. slope. |