


# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 15, T. 26 S., R. 2 W.

CHAINS



from which

A fir, 22 ins. diam., bears S. 71° E., 50 lks. dist.,  
mkd. C N 1/16 S15 BT.

A fir, 12 ins. diam., bears N. 26½° W., 36 lks. dist.,  
mkd. C N 1/16 S15 BT.

Descend 32 ft. over NE. slope.

- 62.15 Leave timber, enter logged area, edge bears E. and W.
- 66.05 Foot of descent, slopes E.; also dirt access road, 15 lks. wide, bears NE. and S. 60° W.; asc. 63 ft. along E. slope.
- 73.75 Top of ascent, slopes E.; desc. 20 ft. along E. slope.
- 75.75 Foot of descent, slopes E.; asc. 42 ft. over SE. slope.
- 80.33 The ¼ sec. cor. of secs. 10 and 15.


From the ¼ sec. cor. of secs. 14 and 15.

S. 89°28' W., on the E. and W. center line of sec. 15.

Descend 16 ft. along S. slope, through scattering timber and dense undergrowth.

- 6.70 Foot of descent, slopes S.; asc. 148 ft. over SE. slope.
- 16.30 Dirt access road, 15 lks. wide, bears N. 30° W. and S. 30° E.
- 17.15 Top of ascent, slopes S.; desc. 22 ft. over SW. slope.
- 19.79 Point for the center E 1/16 sec. cor. of sec. 15.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A cedar, 25 ins. diam., bears N. 28° W., 23 lks. dist.,  
mkd. C E 1/16 S15 BT.

A cedar, 28 ins. diam., bears S. 41° W., 20 lks. dist.,  
mkd. C E 1/16 S15 BT.

Descend 42 ft. over SW. slope.

- 23.70 Foot of descent, slopes S.; asc. 23 ft. along S. slope.
- 29.00 Top of ascent, slopes S.; desc. 46 ft. over SW. slope.
- 33.60 Creek, 5 lks. wide, course S. 20° E.; asc. 8 ft. over SE. slope.
- 35.15 Creek, 2 lks. wide, course SE.; asc. 83 ft. over E. slope.