

# County Surveyor's Record, Douglas County, Oregon

## Subdivision of Section 15, T. 26 S., R. 2 W.

CHAINS	
39.58	The center $\frac{1}{4}$ sec. cor. of sec. 15. Ascend 197 ft. over E. slope.
55.05	Top of ascent, slopes S.; desc. 53 ft. over SW. slope, changing to S. slope.
63.00	Leave timber, enter logged area, edge bears NW. and S.
68.80	Dirt access road, 15 lks. wide, bears N. and SE.
79.10	The $\frac{1}{4}$ sec. cor. of sec. 15 only, on the W. bdy. of sec. 15.
	From the center E 1/16 sec. cor. of sec. 15. N. 1°32' E., on the N. and S. center line of the NE $\frac{1}{4}$ of sec. 15. Ascend 174 ft. over S. slope, changing to SE. slope, through heavy timber and dense undergrowth.
6.60	Gravelled access road, 20 lks. wide, bears NW. and SE.
14.10	Gravelled access road, 20 lks. wide, bears NE. and SW.
20.14	Point for the NE 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the NE $\frac{1}{4}$ . Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. NE 1/16 S 15 1959 from which A cedar, 10 ins. diam., bears N. 15° E., 32 $\frac{1}{2}$ lks. dist., mkd. NE 1/16 S15 BT. A hemlock, 22 ins. diam., bears S. 75 $\frac{1}{2}$ ° W., 34 lks. dist., mkd. NE 1/16 S15 BT.
	Ascend 109 ft. over SW. slope, changing to S. slope, along E. edge of old logged area.
40.25	The E 1/16 sec. cor. of secs. 10 and 15.
	From the N 1/16 sec. cor. of secs. 14 and 15. S. 89°14' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 15. Ascend 72 ft. over SE. slope, through heavy timber and dense undergrowth.
3.00	Leave timber, enter prairie, edge bears NW. and SE.
10.33	Top of ascent, slopes S.; desc. 23 ft. along S. slope.
11.80	Leave prairie, enter timber, edge bears NW. and SE.
15.10	Foot of descent, slopes S.; asc. 25 ft. over SE. slope.
15.95	Gravelled access road, 20 lks. wide, bears NW. and S. curving to SW.
19.81	The NE 1/16 sec. cor. of sec. 15. Descend 124 ft. along S. slope, changing to SW. slope.