

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 17, T. 26 S., R. 2 W.

CHAINS	
	Descend 7 ft. over N. slope, through heavy timber and dense undergrowth.
0.40	Honey Creek, 10 lks. wide, from NE. course W.; asc. 266 ft. over general S. slope.
19.95	Point for the NE 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the NE $\frac{1}{4}$.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NE 1/16 S 17 1959
	from which
	A fir, 8 ins. diam., bears N. 19° E., 13 $\frac{1}{4}$ lks. dist., mkd. NE 1/16 S17 BT.
	A fir, 12 ins. diam., bears S. 68° W., 47 lks. dist., mkd. NE 1/16 S17 BT.
	Ascend 322 ft. over S. slope, changing to SW. slope.
26.60	Leave timber, enter cleared area for transmission line right-of-way, edge bears NW. and SE.
27.60	Dirt access road, 15 lks. wide, bears E. and W. curving to N.; also three-wire transmission line, bears NW. and SE.
30.15	Leave cleared area for transmission line right-of-way, enter timber, edge bears NW. and SE.
38.45	Skid road, 15 lks. wide, bears E. and W.
39.92	The E 1/16 sec. cor. of secs. 8 and 17.
From the N 1/16 sec. cor. of sec. 17 only, on the E. bdy. of sec. 17.	
	S. 87°24' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 17.
	Ascend 205 ft. over E. slope, through heavy timber and dense undergrowth.
6.50	Top of ascent, slopes S.; desc. 102 ft. over S. slope, changing to SW. slope.
7.30	Leave timber, enter cleared area of transmission line right-of-way, edge bears NW. and SE.
9.70	Skid road, 15 lks. wide, bears NW. and SE.
10.70	Three-wire transmission line, bears NW. and SE.; also skid road, 15 lks. wide, bears NW. and SE.
12.05	Creek, 2 lks. wide, course SE.; asc. 102 ft. over E. slope.
13.85	Leave cleared area of transmission line right-of-way, enter timber, edge bears NW. and SE.
15.95	Top of ascent, slopes S.; desc. 61 ft. over SW. slope.
20.00	The NE 1/16 sec. cor. of sec. 17.
	Descend 63 ft. over SW. slope.