

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 6 W.

CHAINS

A fir, 5 ins. diam., bears N. 49° E., 50 lks. dist.,
mkd. T33S R6W S26 BT.

A fir, 23 ins. diam., bears S. 18° E., 48 lks. dist.,
mkd. T33S R6W S35 BT.

A fir, 25 ins. diam., bears S. 38° W., 69 lks. dist.,
mkd. T33S R6W S34 BT.

A fir, 33 ins. diam., bears N. 73° W., 6 lks. dist.,
mkd. T33S R6W S27 BT.

From this point the $\frac{1}{4}$ sec. cor. of secs. 26 and 35 bears N. 89° 52' E.,
39.84 chs. dist.; perpetuated with an iron pipe, $1\frac{1}{4}$ ins. diam.,
extending 8 ins. above the ground, at record bearing and distance
from the original bearing trees:

A rotted oak stump, bears N. 30° E., 12 lks. dist.,
with no marks remaining.

A pine stump, 36 ins. diam., bears S. 25° W., 70 lks. dist.,
marked with a rotted blaze.

and bearing trees marked by Registered Surveyor No. 33.

A fir, 14 ins. diam., bears N. 71° W., 53 lks. dist.,
mkd. $\frac{1}{4}$ S26 RS BT.

A fir, 14 ins. diam., bears S. 50° W., 33 lks. dist.,
mkd. $\frac{1}{4}$ S35 RS BT.

At corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the
ground, with brass cap mkd.

$\frac{1}{4}$ S 26
S 35
T33S R6W
1958

from which new bearing trees:

A fir, 9 ins. diam., bears N. 73° W., 82 lks. dist.,
mkd. $\frac{1}{4}$ S26 BT.

A fir, 9 ins. diam., bears S. 16° E., 57 lks. dist.,
mkd. $\frac{1}{4}$ S35 BT.

Reset iron pipe alongside iron post.

Land, mountainous. Soil, rocky clay. Timber, fir, pine, and ma-
drone; undergrowth, hazel, arrowwood, and poison oak.

N. 0° 19' W., bet. secs. 26 and 27.

Ascend 245 ft. over SE. slope, through heavy timber and dense
undergrowth.

2.50 Dirt road, 20 lks. wide, bears E. and W.

14.85 Spur, slopes N.; desc. 55 ft. over NE. slope.

20.05 Point for the $\frac{1}{16}$ sec. cor. of secs. 26 and 27.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the
ground, with brass cap mkd.