

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 6 W.

CHAINS

S 1/16
 S 27 | S 26
 T33S R6W
 1958

from which

A fir, 21 ins. diam., bears N. 63° E., 11 lks. dist.,
 mkd. S 1/16 S26 BT.

A fir, 5 ins. diam., bears N. 41° W., 12 lks. dist.,
 mkd. S 1/16 S27 BT.

Descend 565 ft. over NE. slope.

- 37.30 Old U. S. Highway No. 99, 30 lks. wide, bears NW. and E.
 38.75 Stream, 5 lks. wide, course N. 20° E.; asc. slightly over SE. slope.
 40.10 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

|
 S27 | S26
 T33S R6W
 1958

from which

A fir, 13 ins. diam., bears N. 17° E., 44 lks. dist.,
 mkd. $\frac{1}{4}$ S26 BT.

A fir, 8 ins. diam., bears N. 56° W., 23 lks. dist.,
 mkd. $\frac{1}{4}$ S27 BT.

Ascend slightly over SE. slope.

- 40.30 Top of ascent, slopes E.; desc. slightly over NE. slope.
 42.15 Stream, 3 lks. wide, course NE.; desc. 140 ft. over NE. slope.
 80.20 The cor. of secs. 22, 23, 26 and 27, perpetuated with an iron bolt, 1 in. diam., extending 4 ins. above ground, firmly set at record bearing and distance from the remaining original bearing trees:

A fir stump, 12 ins. diam., bears S. 43° W., 50 lks. dist.,
 with no marks remaining.

A fir stump, 20 ins. diam., bears N. 60° W., 8 lks. dist.,
 marked with a rotted blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T33S R6W
 S 22 | S 23
 S 27 | S 26
 1958

from which new bearing trees

An oak, 10 ins. diam., bears N. 85° E., 14 lks. dist.,
 mkd. T33S R6W S23 BT.

A fir, 10 ins. diam., bears S. 43° E., 46 lks. dist.,
 mkd. T33S R6W S26 BT.