

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 6 W.

CHAINS

A madrona, 12 ins. diam., bears S. 15° W., 54 lks. dist.,
mkd. T33S R6W S27 BT.

A fir, 4 ins. diam., bears N. 31° W., 48 lks. dist.,
mkd. T33S R6W S22 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, pine, oak, and
madrone; undergrowth, hazel, arrowwood, and poison oak.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.,
determined at record bearing and distance from the remaining orig-
inal bearing trees:

An oak snag, 16 ins. diam., bears N. 62° E., 34 lks. dist.,
mkd. R6W S34.

An oak, 18 ins. diam., bears S. 66° E., 53 lks. dist.,
mkd. with a rotted blaze.

An oak, 18 ins. diam., bears N. 26° W., 12 lks. dist.,
mkd. with an opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the
ground, with brass cap mkd.

T33S R6W
S 33 | S 34
S 4 | S 3
T34S
1958

from which new bearing trees

A fir, 30 ins. diam., bears N. 35° E., 10 lks. dist.,
mkd. T33S R6W S34 BT.

A fir, 30 ins. diam., bears S. 29° E., 36 lks. dist.,
mkd. T34S R6W S3 BT.

A fir, 10 ins. diam., bears S. 30½° W., 50 lks. dist.,
mkd. T34S R6W S4 BT.

A fir, 6 ins. diam., bears N. 36° W., 58 lks. dist.,
mkd. T33S R6W S33 BT.

N. 1° 21' E., bet. secs. 33 and 34.

Ascend 320 ft. over SE. slope, through heavy timber and dense
undergrowth.

20,015

Point for the S. 1/16 sec. cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the
ground, with brass cap mkd.

S 1/16
S 33 | S 34
T33S R6W
1958

from which

A pine, 14 ins. diam., bears N. 54° E., 36 lks. dist.,
mkd. S 1/16 S34 BT.

A pine, 15 ins. diam., bears S. 63° W., 36 lks. dist.,
mkd. S 1/16 S33 BT.