

County Surveyor's Record, Douglas County, Oregon

Dependant Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 6 W.

CHAINS

Ascend slightly over SE. slope.

20.11

Spur, slopes SW.; desc. 105 ft. over NW. slope.

40.03

Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

+
S 33 S 34
T33S R6W
1958

from which

A madrone, 12 ins. diam., bears S. 40° E., 80 lks. dist., mkd. $\frac{1}{4}$ S34 BT.A fir, 14 ins. diam., bears S. 83° W., 37 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

Descend 15 ft. over NW. slope.

42.40

Draw, drains SW.; asc. 245 ft. over SW. slope.

53.70

Spur, slopes W.; desc. 275 ft. over NW. slope.

74.20

Stream, 3 lks. wide, course SW.; asc. 135 ft. over SW. slope.

80.06

Point for the cor. of secs. 27, 28, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T33S R6W
S 28 S 27
S 33 S 34
1958

from which

A fir, 12 ins. diam., bears N. 65° E., 212 lks. dist., mkd. T33S R6W S27 BT.

A madrone, 8 ins. diam., bears S. 72° E., 26 lks. dist., mkd. T33S R6W S34 BT.

A fir, 12 ins. diam., bears S. 76° W., 184 lks. dist., mkd. T33S R6W S33 BT.

A fir, 15 ins. diam., bears N. 33 $\frac{1}{2}$ ° W., 105 lks. dist., mkd. T33S R6W S28 BT.

From this point the cor. of secs. 29, 30, 31, and 32 bears N, 88° 32' W., 158.81 chs. dist., determined at record bearing and distance from the remaining original bearing trees:

A madrone, 24 ins. diam., bears N. 5° E., 40 lks. dist., mkd. S29.

A fir, 36 ins. diam., bears S. 65° W., 12 lks. dist., mkd. T33S R6W S31 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.