

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 6 W.

CHAINS 79.52	The cor. of secs. 27, 28, 33 and 34. Land, mountainous. Soil, rocky clay. Timber, fir, pine, and madrone; undergrowth, hazel, arrowwood, and poison oak.
18.15	N. 1° 05' W., bet. secs. 27 and 28. Ascend 710 ft. over SW. slope, changing to SE. slope, through heavy timber and dense undergrowth.
40.03	Dirt road, 15 lks. wide, bears E. and W. Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 28 S 27 T33S R6W 1958
	from which A chinquapin, 10 ins. diam., bears S. 58° E., 81 lks. dist., mkd. $\frac{1}{4}$ S27 BT. A chinquapin, 15 ins. diam., bears N. 86° W., 37 lks. dist., mkd. $\frac{1}{4}$ S28 BT.
53.34	Ascend 245 ft. over SE. slope. Top of London Peak; desc. 430 ft. over NE. slope, changing to E. slope.
80.84	The cor. of secs. 21, 22, 27, and 28, determined at record bearing and distance from the only remaining original bearing tree: A fir, 32 ins. diam., bears N. 48° E., 42 lks. dist., mkd. with a healed blaze.
	At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked
	T33S R6W S 21 S 22 S 28 S 27 1958
	from which new bearing trees A madrone, 7 ins. diam., bears S. 52 $\frac{1}{2}$ ° E., 16 lks. dist., mkd. T33S R6W S27 BT. An oak, 3 ins. diam., bears S. 39 $\frac{1}{2}$ ° W., 34 lks. dist., mkd. S X BT. A fir, 32 $\frac{1}{2}$ ins. diam., bears N. 5° W., 25 lks. dist., mkd. T33S R6W S21 BT.
	Land, mountainous. Soil, rocky clay. Timber, fir, pine, oak, and madrone; undergrowth, hazel, arrowwood and poison oak.
	From the cor. of secs. 22, 23, 26, and 27. S. 89° 56' W., bet. secs. 22 and 27. Ascend 340 ft. over SE. slope.