

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Sundivisional Lines, T. 33 S., R. 6 W.

CHAINS	Descend 360 ft. over NW. slope.
36.80	Stream, 4 lks. wide, course NE.; asc. 30 ft. over SE. slope.
39.94	Point for the center $\frac{1}{4}$ sec. cor. of sec. 27, at intersection with the E. and W. center line.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.  C $\frac{1}{4}$ S 27 T33S R6W 1958  from which  A fir, 32 ins. diam., bears N. $61^\circ$ E., 54 lks. dist., mkd. C $\frac{1}{4}$ S27 BT.  A fir, 16 ins. diam., bears S. $53\frac{1}{2}^\circ$ W., 93 lks. dist., mkd. C $\frac{1}{4}$ S 27 BT.  Ascend slightly over SE. slope.
47.20	Spur, slopes NE.; desc. 490 ft. over NE. slope.
50.44	The $\frac{1}{4}$ Sec. cor. of secs. 22 and 27.
	From the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.  S. $89^\circ 30'$ W., along the E. and W. center line of sec. 27.  Ascend 330 ft. over SE. slope, changing to NE. slope, through heavy timber and dense undergrowth.
20.00	Point for the center E. $\frac{1}{16}$ sec. cor. of sec. 27.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins diam., 22 ins. in the ground, with brass cap mkd.  E $\frac{1}{16}$ C _____ C S 27 T33S R6W 1958  from which  A madrone, 5 ins. diam., bears N. $60\frac{1}{4}^\circ$ E., 19 lks. dist., mkd. CE $\frac{1}{16}$ S27 BT.  A madrone, 5 ins. diam., bears S. $9\frac{1}{2}^\circ$ E., 49 lks. dist., mkd. CE $\frac{1}{16}$ S27 BT.  Ascend 240 ft. over NE. slope.
34.20	Spur, slopes N.; desc. 110 ft. over NW. slope.
37.90	Stream, 4 lks. wide, course N.; asc. 60 ft. over SE. slope.
40.00	The center $\frac{1}{4}$ sec. cor. of sec. 27. Ascend 620 ft. over SE. slope.
50.01	The $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
	From the E. $\frac{1}{16}$ sec. cor. of secs. 27 and 34.  N. $0^\circ 26'$ W., along the N. and S. center line of the SE $\frac{1}{4}$ of sec. 27.