

# County Surveyor's Record, Douglas County, Oregon

## Dependent Resurvey, Portion of E. Bdy. T. 32 S., R. 4 W.

CHAINS

Deposit basalt stone alongside iron post.

N. 0° 58' E., along the E. bdy. of sec. 24, marking and blazing the true line.

Ascend 50 ft. over SE. slope, through timber and undergrowth.

6.80 Spur, slopes E.; desc. 50 ft. over NE. slope.

9.65 Ravine, drains NE.; asc. 165 ft. over SE. slope.

18.90 Spur, slopes E.; descend slightly over NW. slope.

19.44 Point for the N. 1/16 sec. cor. of sec. 24 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

N 1/16 |  
S 24 |  
1959

from which

A fir, 6 ins. diam., bears S. 40° W., 33 lks. dist., marked N 1/16 S24 BT.

A chinquapin, 8 ins. diam., bears N. 70½° W., 47 lks. dist., marked N 1/16 S24 BT.

Descend 480 ft. over NW. slope.

33.10 Branch, 4 lks. wide, course NE.; asc. 50 ft. over SE. slope.

35.44 The closing cor. of secs. 18 and 19, T. 32 S., R. 3 W., monumented by Mensch with a granite stone, 20x12x8 ins., firmly set, marked CC on E. face, with 3 grooves on N. and S. faces, from which the remaining original bearing tree:

A fir, 54 ins. diam., bears S. 47° E., 53 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

T32S | T32S  
S 24 | S 18  
          | S 19 CC  
R4W | R3W  
1959

from which a new bearing tree

A chinquapin, 5 ins. diam., bears N. 29° E., 39 lks. dist., marked T32S R3W S18 CC BT.

Deposit granite stone alongside iron post.

Ascend 25 ft. over SE. slope.

35.90 Spur, slopes E.; desc. 20 ft. over NE. slope.

37.30 Branch, 2 lks. wide, course E.; asc. 60 ft. over SE. slope.

38.88 The cor. of secs. 13 and 24 only, monumented by Nicklin with a basalt stone, 14x13x6 ins., firmly set, marked with 3 grooves on N. and S. faces, from which the remaining original bearing trees: