

Dependent Resurvey, Portion of E. Bdy., T. 32 S R. 4 W.

CHAINS

A cedar, 47 ins. diam., bears S. 40° W., 11 lks. dist., marked T32S R4W S24 on opened blaze.

A fir, 37 ins. diam., bears N. 57° W., 23 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

T32S
R4W | R3W
S 13 | S 18
S 24 |
1959

from which a new bearing tree

A fir, 13 ins. diam., bears S. 23½° W., 80 lks. dist., marked T32S R4W S24 BT.

Deposit basalt stone alongside iron post.

Dependent Resurvey, Portion of Subdivisional Lines, T. 32 S., R. 4 W.
(Restoring the 1897 survey by Carl S. Nicklin.)

From the ¼ sec. cor., of secs. 23 and 24, monumented with a basalt stone, 12x12x8 ins., firmly set, marked ¼ on W. face, from which the remaining original bearing tree:

A fir snag, 14 ins. diam., bears N. 79° E., 150 lks. dist., marked ¼ S on open blaze.

At the corner point.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked

¼
S 23 | S 24
T32S R4W
1959

from which new bearing trees

A fir, 18 ins. diam., bears N. 62° E., 282 lks. dist., marked ¼ S24 BT.

A fir, 12 ins. diam., bears N. 85° W., 134 lks. dist., marked ¼ S23 BT.

Deposit basalt stone alongside iron post.

N. 0° 35' W., bet. secs. 23 and 24, marking and blazing the true line.

Ascend 20 ft. over SW. slope, through timber and undergrowth.

7.40 Spur, slopes N. 20° W.; desc. 265 ft. over NE. slope.

19.60 Point for the N. 1/16 sec. cor. of secs. 23 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

N 1/16
S 23 | S 24
1959

from which