

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 32 S., R. 4 W.

CHAINS

A fir, 14 ins. diam., bears N. $75\frac{1}{2}^{\circ}$ E., 161 lks. dist.,
marked N 1/16 S24 BT.

A fir, 8 ins. diam., bears N. 52° W., 125 lks. dist.,
marked N 1/16 S23 BT.

Descend 465 ft. over NE. slope.

33.70 Branch, 4 lks. wide, course NW.; desc. 25 ft. over NW. slope.

39.20 The cor. of secs. 13, 14, 23 and 24, monumented with a basalt stone,
14x10x10 ins., firmly set, marked with 1 notch on E. and 3 notches
on S. edge, from which the original bearing trees:

A cedar, 30 ins. diam., bears N. 26° E., 49 lks. dist.,
marked with a healed blaze.

A cedar, 30 ins. diam., bears S. 26° E., 25 lks. dist.,
marked with a healed blaze.

A cedar, 30 ins. diam., bears S. 52° W., 18 lks. dist.,
marked with a healed blaze.

A cedar, 20 ins. diam., bears N. 3° W., 21 lks. dist.,
marked T32S R4W S14 on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap marked

T32S R4W
S 14 S 13
S 23 S 24
1959

Deposit basalt stone alongside iron post.

(Restoring the 1871 survey by William H. Byars,
retraced by Carl S. Nicklin in 1897)

From the cor. of secs. 3 and 4, on the N. bdy. of sec. 10, restored
by the method of broken boundaries, based on the Nicklin retrace-
ment and survey, between the $\frac{1}{4}$ sec. cor. of sec. 4 and the closing
cor. of secs. 3 and 10 on the W. bdy. of sec. 11; there is no re-
maining evidence of the original corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap marked

T32S R4W
S 4 S 3
S 10
1959

from which

A fir, 9 ins. diam., bears N. $5\frac{1}{2}^{\circ}$ E., 39 lks. dist.,
marked T32S R4W S3 BT.

A chinquapin, 8 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ W., 34 lks. dist.,
marked T32S R4W S4 BT.

N. $0^{\circ} 04'$ W., bet. secs. 3 and 4.