

County Surveyor's Record, Douglas County, Oregon

7

Dependent Resurvey, Portion of Subdivisional Line, T. 32 S., R. 4 W.

CHAINS	
	<p>A fir, 7 ins. diam., bears N. 24° W., 49 lks. dist., marked T32S R4W S10 BT.</p> <p>N. 0° 11' E. along the W. bdy. of sec. 11.</p> <p>Descend 1,020 feet over NW. slope, through timber and undergrowth.</p>
31.80	Branch, 2 lks. wide, course W.; ascend 185 ft. over SW. slope.
39.66	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>SET an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked</p> <p style="text-align: center;"> $\frac{1}{4}$ S 10 S 11 T32S R4W 1959 </p> <p>from which</p> <p>A fir, 8 ins. diam., bears S. 52$\frac{1}{2}$° E., 3 lks. dist., marked $\frac{1}{4}$ S11 BT.</p> <p>A madrona, 8 ins. diam., bears West, 20 lks. dist., marked $\frac{1}{4}$ S10 BT.</p> <p>Ascend 390 ft. over SW. slope.</p>
55.50	Ridge, bears NW. and SE.; desc. 35 ft. over NE. slope.
59.49	<p>Point for the N. 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked</p> <p style="text-align: center;"> N 1/16 S 10 S 11 1959 </p> <p>from which</p> <p>A madrona, 12 ins. diam., bears N. 87$\frac{1}{2}$° E., 16 lks. dist., marked N 1/16 S11 BT.</p> <p>A fir, 10 ins. diam., bears N. 51° W., 31 lks. dist., marked N 1/16 S10 BT.</p> <p>Descend 230 ft. over NE. slope.</p>
71.09	<p>The closing cor. of secs. 3 and 10, hereinafter described.</p> <p>Descend slightly over NE. slope.</p>
71.38	Ravine, drains SE.; asc. 140 ft. over SE. slope.
75.78	Spur, slopes E.; desc. 105 ft. over NE. slope.
79.32	<p>The NW. cor. of sec. 11, determined at record bearing and distance from the original bearing tree:</p> <p>A fallen fir, 30 ins. diam., bears S. 48° E., 63 lks. dist., marked with a healed blaze.</p> <p>At the corner point.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked</p>