

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, portion of the Subdivisional Lines, T. 32 S., R. 4 W.

CHAINS

T32S R4W
S 3
| S 11
1959

from which a new bearing tree

A fir, 36 ins. diam., bears S. $15\frac{3}{4}^{\circ}$ E., 61 lks. dist.,
marked T32S R4W S11 BT.

Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, pine,
cedar, madrona and chinquapin; undergrowth, manzanita, huckle-
berry and rhododendron.

From the cor. of secs. 10, 11, 14 and 15.

S. $89^{\circ} 19'$ W., bet. secs. 10 and 15.Descend 1, 220 ft. over W. slope, changing to NW. slope, through
timber and undergrowth.39.67 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate
distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap marked

$\frac{1}{4}$ S 10
S 15
T32S R4W
1959

from which

A fir, 6 ins. diam., bears N. $2\frac{1}{4}^{\circ}$ W., 49 lks. dist.,
marked $\frac{1}{4}$ S10 BT.

A fir, 8 ins. diam., bears S. $48\frac{3}{4}^{\circ}$ E., 22 lks. dist.,
marked $\frac{1}{4}$ S15 BT.

Descend 250 ft. over NW. slope.

53.55 Whitehorse Creek, 20 lks. wide, course N.; asc. 445 ft. over SE.
slope.79.34 The cor. of secs. 9, 10, 15 and 16, determined at record bearing
and distance from the remaining original bearing trees:

A fallen fir, 30 ins. diam., bears S. 43° E., 83 lks. dist.,
marked BT on opened blaze.

A fallen fir, 18 ins. diam., bears N. 75° W., 69 lks. dist.,
marked S9 BT on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap marked

T32S R4W
S 9 | S 10
S 16 | S 15
1959

from which new bearing trees

A fir, 10 ins. diam., bears N. 84° E., 41 lks. dist.,
marked T32S R4W S10 BT.

A fir, 8 ins. diam., bears S. $32\frac{1}{4}^{\circ}$ E., 55 lks. dist.,
marked T32S R4W S15 BT.