

County Surveyor's Record, Douglas County, Oregon

12

Subdivision of Section 24, T. 32.S., R. 4 W.

CHAINS

40.57

Point for the center $\frac{1}{4}$ sec. cor. of sec. 24, at intersection with the E. and W. center line of sec. 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked.

C $\frac{1}{4}$ S 24
1959

from which

A fir, 14 ins. diam., bears N. 59° E., 4 lks. dist., marked C $\frac{1}{4}$ S24 BT.

A fir, 5 ins. diam., bears N. 53° W., 27 lks. dist., marked C $\frac{1}{4}$ S24 BT.

The E. and W. center line of sec. 24 was surveyed to determine the point for the center $\frac{1}{4}$ sec. cor. The bearing of the line was found to be West, but no measurement was made.

Descend 485 ft. over NE. slope.

60.33

Point for the center N $\frac{1}{16}$ sec. cor. of sec. 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

C
N $\frac{1}{16}$ | S 24
C
1959

from which

A hemlock, 6 ins. diam., bears N. 73° E., 79 lks. dist., marked CN $\frac{1}{16}$ S24 BT.

A fir, 6 ins. diam., bears S. 40° W., 13 lks. dist., marked CN $\frac{1}{16}$ S24 BT.

Descend 65 ft. over NE. slope.

80.09

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with a basalt stone, 12x10x6 ins., firmly set, marked $\frac{1}{4}$ on N. face, from which the remaining original bearing tree:

A fir snag, 30 ins. diam., bears S. 80° W., 31 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 13
 $\frac{1}{4}$ S 24
T32S R4W
1959

from which new bearing trees

A chinquapin, 6 ins. diam., bears N. 63° W., 24 lks. dist., marked $\frac{1}{4}$ S 13 BT.

A chinquapin, 6 ins. diam., bears S. $7\frac{1}{2}^{\circ}$ E., 43 lks. dist., marked $\frac{1}{4}$ S24 BT.

Deposite basalt stone alongside iron post.