

Subdivision of Section 10, T. 32 S. R. 4 W.

CHAINS

From the  $\frac{1}{4}$  sec. cor. of secs. 10 and 15.


N.  $0^{\circ} 15' E.$ , along the N. and S. center line of sec. 10, marking and blazing the true line.

Descend 130 ft. over broken NW. slope, through timber and undergrowth.

19.98

Point for the center S  $\frac{1}{16}$  sec. cor. of sec. 10.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap marked



from which

A fir, 5 ins. diam., bears N.  $89^{\circ} E.$ , 16 lks. dist., marked CS  $\frac{1}{16}$  S10 BT.

A fir, 8 ins. diam., bears N.  $49^{\circ} W.$ , 5 lks. dist., marked CS  $\frac{1}{16}$  S10 BT.

Descend 90 ft. over NW. slope.


25.25

Branch, 2 lks. wide, course SW.; asc. 110 ft. over SW. slope.

39.96

Point for the center  $\frac{1}{4}$  sec. cor. of sec. 10, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap marked



from which

A fir, 8 ins. diam., bears N.  $81^{\circ} E.$ , 19 lks. dist., marked C $\frac{1}{4}$  S10 BT.

A fir, 12 ins. diam., bears N.  $78\frac{1}{2}^{\circ} W.$ , 34 lks. dist., marked C $\frac{1}{4}$  S10 BT.


The E. and W. center line of sec. 10 was surveyed to determine the point for the center  $\frac{1}{4}$  sec. cor. This line was found to bear S,  $89^{\circ} 39' W.$ , but no measurement was made.

Ascend 45 ft. over broken SW. slope.

59.84

Point for the center N  $\frac{1}{16}$  sec. cor. of sec. 10.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap marked



from which

A fir, 8 ins. diam., bears N.  $8^{\circ} E.$ , 25 lks. dist., marked CN  $\frac{1}{16}$  S10 BT.

A madrona, 5 ins. diam., bears N.  $85^{\circ} W.$ , 105 lks. dist., marked CN  $\frac{1}{16}$  S10 BT.

Ascend 220 ft. over SW. slope.