

Subdivison of Section 10, T. 32 S., R. 4 W.

CHAINS
71.25

The $\frac{1}{4}$ sec. cor. of sec. 10 only, on the N. bdy. of sec. 10.

Remonumentation of Corners on E. Bdy. of T. 32 S., R. 4 W.
(Original corners established by William H. Byars in 1871
and Carl S. Nicklin in 1897.)

The following is the remonumentation of certain original corner points, T. 32 S., R. 4 W., Will. Mer., Oregon, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, With New Accessories When Needed."

The cor. of secs. 24 and 25, monumented by Nicklin in 1897 with a basalt stone, firmly set, 14x8x8 ins., no marks remaining, from which the original 1897 bearing trees:

A fir, 24 ins. diam., bears N. 58° E., 87 lks. dist., marked with a healed blaze.

A fir snag, 48 ins. diam., bears S. 80° E., 61 lks. dist., marked with an opened blaze.

A fallen cedar, 30 ins. diam., bears S. 62° W., 34 lks. dist., marked with a healed blaze.

A pine snag, 50 ins. diam., bears N. 62° W., 70 lks. dist., marked S24 on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

T32S T32S
S 24 |
S 25 | S 19
R4W R3W
1959

from which new bearing trees

A fir, 5 ins. diam., bears N. 50° W., 20 lks. dist., marked T32S R4W S24 BT.

A cedar, 30 ins. diam., bears S. 48° W., 77 lks. dist., marked T32S R4W S25 BT.

Deposit basalt stone alongside iron post.

The cor. of secs. 7, 12, 13 and 18, determined at record bearing and distance from each of the remaining bearing trees marked by Byars in 1871,

A fir, 25 ins. diam., bears N. 32° E., 76 lks. dist., marked with a healed blaze.

A fallen fir, 38 ins. diam., bears N. 28° W., 31 lks. dist., no marks remaining.

and bearing trees marked in 1897 by Carl S. Nicklin

A fir, 36 ins. diam., bears S. 73° E., 53 lks. dist., marked with a healed blaze. (Record, bears S. 72° E., 56 lks. dist.)

At the corner point