

Remonumentation of Corners on E. Bdy. of T. 32 S., R. 4 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

T32S	
R4W	R3W
S 12	S 7
S 13	S 18
1959	

from which new bearing trees

A fir, 55 ins. diam., bears S. 77° W., 50 lks. dist., marked T32S R4W S13 BT.

A hemlock, 10 ins. diam., bears N. 50° W., 62 lks. dist., marked T32S R4W S12 BT.

The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, determined at record bearing and distance from the remaining original bearing tree marked by Byars in 1871:

A fir, 24 ins. diam., bears S. 85° W., 31 lks. dist., marked $\frac{1}{4}$ S on bark.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

$\frac{1}{4}$	
S 12	S 7
R4W	R3W
T32S	
1959	

from which a new bearing tree

A fir, 18 ins. diam., bears N. $56\frac{1}{4}^{\circ}$ E., 66 lks. dist., marked $\frac{1}{4}$ S7 BT.

The cor. of secs. 1, 6, 7 and 12, determined at record bearing and distance from each of the bearing trees marked in 1897 by Carl S. Nicklin:

A fir, 36 ins. diam., bears S. 8° E., 214 lks. dist., marked S7 on opened blaze.

A fir, 45 ins. diam., bears S. $8\frac{1}{2}^{\circ}$ W., 166 lks. dist., marked R4W on opened blaze.

A fir, 38 ins. diam., bears N. 18° W., 108 lks. dist., marked BT on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

T32S	
R4W	R3W
S 1	S 6
S 12	S 7
1959	

from which a new bearing tree

A fir, 10 ins. diam., bears N. 36° E., 44 lks. dist., marked T32S R3W S6 BT.