

County Surveyor's Record, Douglas County, Oregon

16

Remonumentation of Corners on N. Bdy. of T. 32 S., R. 4 W.

CHAINS

Remonumentation of Corners on N. Bdy. of T. 32 S., R. 4 W.
(Original corners established by William H. Byars in 1871.)

The cor. of secs. 2, 3, 34 and 35, perpetuated with an axle shaft,
1 in. diam., set by the County Surveyor in 1950, from which a bearing
tree marked in 1950:

A fir, 12 ins. diam., bears S. 62° E., 91 lks. dist.,
marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap marked

T31S R4W
S 34 S 35
S 3 S 2
T32S
1959

from which new bearing trees

A cedar, 14 ins. diam., bears N. 30° E., 134 lks. dist.,
marked T31S R4W S35 BT.

An alder, 10 ins. diam., bears S. 40 $\frac{1}{2}$ ° W., 74 lks. dist.,
marked T32S R4W S3 BT.

A fir, 5 ins. diam., bears N. 70 $\frac{1}{2}$ ° W., 147 lks. dist.,
marked T31S R4W S34 BT.

Reset axle shaft alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, determined at record bearing and
distance from each of the original bearing trees:

A madrona, 12 ins. diam., bears N. 50° W., 9 lks. dist.,
marked $\frac{1}{4}$ S on opened blaze.

A fir, 44 ins. diam., bears South, 45 lks. dist., marked
 $\frac{1}{4}$ S3 BT on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground,
with brass cap marked

T31S
S 34
$\frac{1}{4}$ S 3
T32S R4W
1959

from which new bearing trees

A fir, 22 ins. diam., bears N. 42° E., 37 lks. dist.,
marked $\frac{1}{4}$ S34 BT.

A fir, 20 ins. diam., bears S. 25° E., 48 lks. dist.,
marked $\frac{1}{4}$ S3 BT.

The $\frac{1}{4}$ sec. cor., of secs. 4 and 33, determined at record bearing and
distance from the remaining original bearing tree:

A sawed fir stump, 40 ins. diam., bears S. 80° W., 23 lks. dist.,
marked with a rotted blaze.