

County Surveyor's Record, Douglas County, Oregon

17

Remonumentation of Corners on N. Bdy. of T. 32 S., R. 4 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked
$$\begin{array}{r} T31S \\ \frac{1}{4} \frac{S 33}{S 4} \\ T32S R4W \\ 1959 \end{array}$$

from which new bearing trees

A fir, 22 ins. diam., bears N. 9° E., 129 lks. dist., marked $\frac{1}{4}$ S33 BT.A cedar, 18 ins. diam., bears S. $42\frac{1}{2}^\circ$ W., 52 lks. dist., marked $\frac{1}{4}$ S4 BT.

The cor. of secs. 4, 5, 32 and 33, perpetuated with an iron pipe, $\frac{3}{4}$ in. diam., set by the County Surveyor in 1950, from which bearing trees marked in 1950:

A maple, 10 ins. diam., bears N. $39\frac{1}{4}^\circ$ E., 76 lks. dist., marked T31S R4W S33 CS BT.A fir, 14 ins. diam., bears N. $45\frac{1}{4}^\circ$ W., 50 lks. dist., marked T31S R4W S32 CS BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. dia., 20 ins. in the ground, with brass cap marked
$$\begin{array}{r} T31S R4W \\ S 32 | S 33 \\ \hline S 5 | S 4 \\ 1959 \end{array}$$

from which new bearing trees

A fir, 8 ins. diam., bears S. 72° E., 25 lks. dist., marked T32S R4W S4 BT.A fir, 10 ins. diam., bears S. 22° W., 26 lks. dist., marked T32S R4W S5 BT.A fir, 10 ins. diam., bears N. 70° W., 28 lks. dist., marked T31S R4W S32 BT.

Reset iron pipe alongside iron post.

The cor. of secs. 5, 6, 31 and 32, remonumented with an iron pipe, $\frac{3}{4}$ in. diam., set by County Surveyor in 1950, from which the remaining original bearing tree:

A sawed fir stump, 36 ins. diam., bears N. 52° E., 29 lks. dist., marked BT on opened blaze.

and bearing trees marked in 1950

A chinquapin, 8 ins. diam., bears N. 45° E., 65 lks. dist., marked T31S R4W S32 CS BT.A madrona, 6 ins. diam., bears S. 51° E., 35 lks. dist., marked T32S R4W S5 CS BT.A madrona, 6 ins. diam., bears S. 33° W., 41 lks. dist., marked T32S R4W S6 CS BT.