

Remonumentation of Corners on N. Bdy. of T. 32 S., R. 4 W.

CHAINS

A madrona, 8 ins. diam., bears N. 35° W., 14 lks. dist.,  
T31S R4W S31 CS BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the  
ground, with brass cap marked

T31S R4W  
S 31 | S 32  
S 6 | S 5  
T32S  
1959

FD OK  
7/19/94  
1995-0115 AFB  
K. T. ...

Reset iron pipe alongside iron post.

Remonumentation of Subdivisional Corners in T. 32 S., R. 4 W.  
(Original corners established or remonumented  
by Carl S. Nicklin in 1897.)

The ¼ sec. cor. of secs. 35 and 36, monumented with a basalt stone,  
12x8x8 ins., firmly set, marked ¼ on W. face, from which the re-  
maining original bearing trees:

A sawed cedar stump, 24 ins. diam., bears N. 75° E., 99 lks.  
dist., no marks remaining.

A pine, 36 ins. diam., bears S. 75° W., 17 lks. dist., with  
visible scribe marks.

and a bearing tree marked by Registered Surveyor 33;

A pine, 12 ins. diam., bears N. 46° E., 85 lks. dist.,  
marked ¼ S36 RS 33 BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. dia., 20 ins. in the  
ground, with brass cap marked

↑  
S 35 | S 36  
T32S R4W  
1959

Deposit basalt stone alongside iron post.

The cor. of secs. 25, 26, 35 and 36, monumented with a basalt stone,  
12x10x8 ins., firmly set, no marks remaining, from which the re-  
maining original bearing trees:

A cedar, 30 ins. diam., bears N. 20° E., 278 lks. dist.,  
marked T32S R4W S25 BT on open blaze.

A cedar, 18 ins. diam., bears S. 88° W., 69 lks. dist.,  
marked T32S R4W S35 BT. on open blaze.

A pine, 26 ins. diam., bears N. 9° W., 247 lks. dist.,  
marked T32S R4W S26 BT on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the  
ground, with brass cap marked