

County Surveyor's Record, Douglas County, Oregon

19

Remonumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

T32S R4W
 S 26 | S 25
 S 35 | S 36
 1959

from which new bearing trees

A cedar, 6 ins. diam., bears N. 33° E., 24 lks. dist.,
 marked T32S R4W S25 BT.

A cedar, 7 ins. diam., bears S. 54° E., 28 lks. dist.,
 marked T32S R4W S36 BT.

A fir, 14 ins. diam., bears S. 43° W., 10 lks. dist.,
 marked T 32S R4W S35 BT.

A fir, 6 ins. diam., bears N. 50° W., 13 lks. dist.,
 marked T32S R4W S26 BT.

Deposit basalt stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with a basalt stone,
 20x12x8 ins., firmly set, marked $\frac{1}{4}$ on W. face, from which the re-
 maining original bearing tree:

A cedar, 18 ins. diam., bears N. 54° E., 26 lks. dist.,
 marked $\frac{1}{4}$ S on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the
 ground, with brass cap marked

$\frac{1}{4}$
 S 26 | S 25
 T32S R4W
 1959

from which new bearing trees

A fir, 14 ins. diam., bears N. 76° E., 48 lks. dist.,
 marked $\frac{1}{4}$ S25 BT.

A cedar, 12 ins. diam., bears S. 1° W., 63 lks. dist.,
 marked $\frac{1}{4}$ S26 BT.

Deposit basalt stone alongside iron post.

The cor. of secs. 23, 24, 25 and 26, monumented with a basalt stone,
 12x10x8 ins., firmly set, marked with 2 notches on the S. and 1
 notch on the E. edges, from which the remaining original bearing
 trees:

A pine, 34 ins. diam., bears N. 43° E., 30 lks. dist.,
 marked T32S R4W S24 BT.

A pine, 36 ins. diam., bears S. 58° E., 52 lks. dist.,
 marked T32S R4W S25 BT.

A pine snag, 18 ins. diam., bears S. 56° W., 59 lks. dist.,
 marked T32S R4W S26 BT on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the
 ground to solid rock, and in a mound of stone, 3 ft. base, to top,
 with brass cap marked

T32S R4W
 S 23 | S 24
 S 26 | S 25
 1959

FD OK PER NYBREN
 C.S. 63/51 NOV. 1989