

Remonumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

from which new bearing trees

A fir, 23 ins. diam., bears S. 14° W., 114 lks. dist.,
marked T32S R4W S26 BT.

A cedar, 15 ins. diam., bears N. 87° W., 86 lks. dist.,
marked T32S R4W S23 BT.

Deposit basalt stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with a basalt stone, 14x8x6 ins., firmly set, marked $\frac{1}{4}$ on W. face, from which the remaining original bearing tree:

A rotted fir stump, 24 ins. diam., bears N. 70° E., 12 lks. dist., no marks remaining.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked

$\frac{1}{4}$
S 14 | S13
T32S R4W
1959

from which new bearing trees

A fir, 6 ins. diam., bears N. 75° E., 38 lks. dist.,
marked $\frac{1}{4}$ S13 BT.

A fir, 9 ins. diam., bears N. 61° W., 50 lks. dist.,
marked $\frac{1}{4}$ S14 BT.

Deposit basalt stone alongside the iron post.

The cor. of secs. 11, 12, 13 and 14, determined at record bearing and distance from each of the original bearing trees:

A fir snag, 24 ins. diam., bears N. 7° E., 66 lks. dist.,
marked S12 on opened blaze.

A fir, 28 ins. diam., bears S. 46° E., 64 lks. dist.,
marked R4 on opened blaze.

A fir snag, 36 ins. diam., bears S. 40° W., 144 lks. dist.,
marked B on opened blaze.

A fir, 38 ins. diam., bears N. 70° W., 102 lks. dist.,
marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap marked

T32S R4W
S11 | S 12
S14 | S 13
1959

from which new bearing trees

A fir, 8 ins. diam., bears N. 39° E., 29 lks. dist.,
marked T32S R4W S12 BT.

A fir, 12 ins. diam., bears S. 27 $\frac{1}{2}$ ° W., 95 lks. dist.,
marked T32S R4W S14 BT.