

## County Surveyor's Record, Douglas County, Oregon

21

## Remonumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, determined at record bearing and distance from the remaining original bearing tree:

A fir, 36 ins. diam., bears S. 80° W., 39 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S 12  
S 13  
T32S R4W  
1959

from which a new bearing tree

A fir, 12 ins. diam., bears N. 44° E., 97 lks. dist., marked  $\frac{1}{4}$  S12 BT.

The cor. of secs. 1 and 2 on the N. bdy. of sec. 12, remonumented with an iron post, 1 in. diam., extending 13 ins. above ground, with brass cap marked County Surveyors Office T32S R4W closing cor. secs. 1 and 2 1957, from which bearing trees marked by Nicklin in 1897:

A fir, 12 ins. diam., bears N. 27° E., 23 lks. dist., marked with a healed blaze.

A fir, 24 ins. diam., bears N. 63° W., 70 lks. dist., marked with a healed blaze.

and a bearing tree marked in 1957:

A fir, 12 ins. diam., bears N. 71° E., 37 lks. dist., marked T32SR4W S1 CS BT.

At corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap marked

T32S R4W  
S 2 | S 1  
S 12  
1959

Deposit County post alongside iron post.

The closing cor. of secs. 11 and 12, on the S. bdy of sec. 2, monumented with an iron post, 1 in. diam., extending 10 ins. above ground, with brass cap marked

County Surveyors Office  
T32S R4W  
Clos. Cor.  
Sec 2  
II | 12  
1957

from which the remaining original bearing tree:

A fir snag, 26 ins. diam., bears S. 55° W., 75 lks. dist., marked T32S R4W on opened blaze.

and bearing trees marked in 1957

A hemlock, 6 ins. diam., bears S.  $19\frac{1}{2}$ ° W., 49 lks. dist., marked T32S R4W S12 CC CS BT.