

## County Surveyor's Record, Douglas County, Oregon

22

## Remonumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

A fir, 26 ins. diam., bears N. 42° W., 76 lks. dist.,  
marked T32S R4W S11 CC CS BT.

Stamp BIM on brass cap.

The cor. of secs. 26, 27, 34 and 35, determined at record bearing  
and distance from the remaining original bearing tree:

A cedar, 20 ins. diam., bears S. 32° W., 25 lks. dist.,  
marked with portions of scribed marks on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the  
ground, with brass cap marked

T32S R4W
S 27   S 26
S 34   S 35
1959

from which new bearing trees

A fir, 14 ins. diam., bears N. 29½° E., 116 lks. dist.,  
marked T32S R4W S26 BT.

A fir, 14 ins. diam., bears S. 71° E., 113 lks. dist.,  
marked T32S R4W S35 BT.

A fir, 26 ins. diam., bears S. 3° W., 80 lks. dist.,  
marked T32S R4W S34 BT.

A fir, 5 ins. diam., bears N. 81° W., 38 lks. dist.,  
marked T32S R4W S27 BT.

The ¼ sec. cor. of secs. 26 and 35, monumented with a basalt stone,  
12x8x8 ins., marked ¼ on N. face, from which the original bearing  
trees:

A cedar snag, 30 ins. diam., bears N. 46° W., 75 lks. dist.,  
marked BT on opened blaze.

A cedar, 36 ins. diam., bears S. 19° W., 39 lks. dist.,  
marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the  
ground, with brass cap marked

¼ S 26
¼ S 35
T32S R4W
1959

FDOK PER NYGREN  
C.S. 63/51 NOV. 1989

from which a new bearing tree.

A fir, 20 ins. diam., bears N. 80° E., 107 lks. dist.,  
marked ¼ S26 BT.

Deposit basalt stone alongside iron post.

The ¼ sec. cor. of secs. 26 and 27, monumented with a basalt stone,  
14x10x8 ins., marked ¼ on N. face, from which the original bearing  
trees:

A sawed fir stump, 26 ins. diam., bears N. 34° E., 42 lks. dist.,  
marked with portions of scribed marks on opened blaze.