

County Surveyor's Record, Douglas County, Oregon

Re monumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

A fir snag, 40 ins. diam., bears N. 67° W., 32 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

$\frac{1}{4}$
 S 27 | S 26
 T32S | R4W
 1959

from which new bearing trees

A fir, 36 ins. diam., bears N. 45° W., 119 lks. dist., marked $\frac{1}{4}$ S 27 BT.

A fir, 22 ins. diam., bears S. 8° W., 179 lks. dist., marked $\frac{1}{4}$ S27 BT.

No suitable tree is available in sec. 26.

Deposit basalt stone alongside iron post.

The cor. of secs. 22, 23, 26 and 27, determined at record distance from each of the remaining original bearing trees:

A cedar, 32 ins. diam., bears N. 22½° E., 49 lks. dist., marked with portions of scribed marks on opened blaze. (Record bearing, N. 42½° E.)

A cedar, 20 ins. diam., bears S. 72° W., 41 lks. dist., marked with an opened blaze.

A sawed fir stump, 40 ins. diam., bears N. 57° W., 61 lks. dist., marked with a healed blaze. (Record bearing, N. 51° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

T32S R4W
 S 22 | S 23
 S 27 | S 26
 1959

FJ OK PER NYGREN
 CS 63/51 NOV. 1989

from which new bearing trees

A cedar, 32 ins. diam., bears S. 5° E., 79 lks. dist., marked T32S R4W S26 BT.

A fir, 50 ins. diam., bears N. 49° W., 98 lks. dist., marked T32S R4W S22 BT.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, determined at record bearing and distance from the remaining original bearing tree:

A fir, 50 ins. diam., bears N. 15° W., 23 lks. dist., marked with an opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked