

Re monumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

$\frac{1}{4}$
 S 22 | S 23
 T32S R4W
 1959

from which new bearing trees

A fir, 20 ins. diam., bears N. 69° E., 47 lks. dist.,
 marked $\frac{1}{4}$ S23 BT.

A fir, 48 ins. diam., bears S. 19° W., 44 lks. dist.,
 marked $\frac{1}{4}$ S22 BT.

The cor. of secs. 14, 15; 22 and 23, determined at record bearing
 and distance from each of the original bearing trees:

A fir snag, 30 ins. diam., bears N. 32° E., 27 lks. dist.,
 marked with a burned blaze.

A fir, 30 ins. diam., bears S. 30° E., 57 lks. dist.,
 marked with a burned blaze.

A fir snag, 26 ins. diam., bears S. 52 $\frac{1}{2}$ ° W., 17 lks. dist.,
 marked with a burned blaze.

A fir snag, 36 ins. diam., bears N. 45° W., 69 lks. dist.,
 marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the
 ground, with brass cap marked

T32S R4W
 S 15 | S 14
 S 22 | S 23
 1959

from which new bearing trees

A madrona, 11 ins. diam., bears N. 32° E., 83 lks. dist.,
 marked T32S R4W S14 BT.

A madrona, 6 ins. diam., bears S. 60° E., 71 lks. dist.,
 marked T32S R4W S23 BT.

A cedar, 28 ins. diam., bears S. 6° W., 81 lks. dist.,
 marked T32S R4W S22 BT.

A cedar, 44 ins. diam., bears N. 20° W., 78 lks. dist.,
 marked T32S R4W S15 BT.

The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, determined at record bearing
 and distance from each of the original bearing trees:

A sawed fir stump, 34 ins. diam., bears N. 4° E., 22 lks.
 dist., marked with a healed blaze.

A fir, 15 ins. diam., bears S. 65° W., 34 lks. dist.,
 marked with a healed blaze.

At the corner point.

Set and iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the
 ground, with brass cap marked