

County Surveyor's Record, Douglas County, Oregon

25

Remonumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

$$\frac{1}{4} \frac{S 14}{S 23}$$

T32S R4W
1959

from which a new bearing tree

A hemlock, 14 ins. diam., bears N. 31° E., 74 lks. dist.,
marked $\frac{1}{4}$ S14 BT.

The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with a basalt stone,
14x12x8 ins., marked $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap marked

$$\frac{1}{4} \frac{S 15}{S 14}$$

T32S R4W
1959

from which

A fir, 8 ins. diam., bears N. 61° E., 20 lks. dist.,
marked $\frac{1}{4}$ S14 BT.

A fir, 8 ins. diam., bears N. 50 $\frac{1}{2}$ ° W., 32 lks. dist.,
marked $\frac{1}{4}$ S15 BT.

Deposit basalt stone alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, determined at record bearing
and distance from the remaining original bearing tree:

A fir, 34 ins. diam., bears S. 29° E., 16 lks. dist.,
marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap marked

$$\frac{1}{4} \frac{S 22}{S 27}$$

T32S R4W
1959

from which a new bearing tree

A fir, 8 ins. diam., bears N. 65° W., 111 lks. dist.,
marked $\frac{1}{4}$ S22 BT.

The cor. of secs. 15, 16, 21 and 22, determined at record bearing
and distance from each of the original bearing trees:

A madrona, 15 ins. diam., bears N. 70° E., 46 lks. dist.,
marked T32S R4W S15 on opened blaze.

A fir, 30 ins. diam., bears S. 60° E., 67 lks. dist.,
marked with a healed blaze.

A fir, 30 ins. diam., bears S. 34° W., 30 lks. dist.,
marked with a healed blaze.