

Remonumentation of Subdivisional Corners in T. 32 S., R. 4 W.

CHAINS

A fir snag, 24 ins. diam., bears N. 63° W., 33 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

T32S R4W
S 16 | S 15
S 21 | S 22
1959

from which new bearing trees

A fir, 25 ins. diam., bears N. 44½° E., 91 lks. dist., marked T32S R4W S15 BT.

A fir, 14 ins. diam., bears N. 44½° W., 139 lks. dist., marked T32S R4W S16 BT.

The ¼ sec. cor. of secs. 15 and 22, determined at record bearing and distance from the remaining original bearing tree:

A pine, 30 ins. diam., bears N. 46½° E., 108 lks. dist., with partial scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

¼ S 15
¼ S 22
T32S R4W
1959

from which new bearing tree

A fir, 30 ins. diam., bears S. 25° E., 189 lks. dist., marked ¼ S22 BT.

The ¼ sec. cor. of secs. 15 and 16, determined at record bearing and distance from the remaining original bearing tree:

A fir, 20 ins. diam., bears S. 27° W., 69 lks. dist., marked ¼ S on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap marked

¼ S 16 | S 15
T32S R4W
1959

from which new bearing trees

A fir, 18 ins. diam., bears S. 47¼° E., 73 lks. dist., marked ¼ S15 BT.

A pine, 5 ins. diam., bears S. 57¾° W., 20 lks. dist., marked ¼ S16 BT.